




The next step in the evolution of low speed
high torque (LSHT) hydraulic motors.


VIS Motors

Highlights

Product Description

The VIS (Valve-in-Star) Motors are the next step in the evolution of the low speed high torque (LSHT) hydraulic motors. The VIS design provides design advantages over other types of LSHT hydraulic motor valving resulting in a more compact package with better efficiency and higher pressure capability. These improvements have shown significant packaging and performance advantages in applications such as skid steer loaders, mini excavators, trenchers and logging equipment.

VIS motors are primarily intended for use in closed loop circuit applications. Consult your Eaton representative for assistance on open loop circuit applications.



Features, Benefits, and Applications

Features

- Patented VIS Geroler technology
- Simplified design - only three moving components:
 - geroler star
 - drive
 - output shaft
- Pressure-balance Geroler - improves efficiency
- Shuttle valve option for reliable internal drive lubrication
- Variety of optional features

Benefits

- Extremely compact powerful package
- Highest output torque in its class
- High efficiency
- Reduced system temperatures
- High horsepower density
- Design flexibility
- Reliable and dependable performance


Applications

- Skid steer loaders
- Sprayers
- Underground boring equipment
- Forestry equipment
- Irrigation reels
- Grinders/Mixers
- Material handling equipment
- Augers and skid steer attachments
- Large turf care equipment

Design Features


Eaton hydraulic motors provide design flexibility. All VIS motors are available with various configurations consisting of:

- Displacement (Geroler)
- Output Shaft
- No Shaft (Bearingless Motor)
- Port Configuration
- Mounting Flange
- Park brake
- Other Special Features




Standard Motor

The standard motor mounting flange is located as close to the output shaft as possible. This type of mounting supports the motor close to the shaft load. This mounting flange is also compatible with many standard gear boxes.



Wheel Motor

The wheel motor mounting flange is located near the center of the motor which permits part or all of the motor to be located inside the wheel or roller hub. In traction drive applications, loads can be positioned over the motor bearings for best bearing life. This wheel motor mounting flange provides design flexibility in many applications.



Bearingless Motor

The bearingless motor has the same drive components as the standard and wheel motors with the exception that the motor is assembled without the output shaft, bearings and bearing housing. The bearingless motor is especially suited for applications such as gear boxes, winch drives, reel and roll drives. Bearingless motor applications must be designed with a bearing supported internal spline to mate with the bearingless motor drive. Product designs using these hydraulic motors provide considerable cost savings.

D-1

D-2

Table of Contents

Highlights	D-ii
Features, Benefits, and Applications	D-iii
Table of Contents	D-iv
Typical Hydraulic Circuit	D-v

VIS 40 Series

Highlights	D-2-1
Specifications	D-2-2
Performance Data	D-2-3
Dimensions	D-2-6
Installation Information	D-2-10
Dimensions Shafts	D-2-11
Side Load Capacity	D-2-12
Oversize Flange 224,0 [8.82] B.C.	D-2-14
Product Numbers	D-2-17
Model Code	D-2-19

VIS 40 Series Two-speed

Specifications	D-2-20
Performance Data	D-2-20
Dimensions	D-2-21
Installation Information	D-2-25
Product Numbers	D-2-26
Model Code	D-2-27
Brake Description	D-2-28
Brake Shaft Dimensions/ Sideload Curves	D-2-30

VIS 45 Series

Highlights	D-3-1
Specifications	D-3-2
Performance Data	D-3-3
Dimensions	D-3-6
Installation Information	D-3-9
Dimensions Shafts	D-3-10
Side Load Capacity	D-3-12


Product Numbers	D-3-13
Model Code	D-3-15
VIS 45 Series Two-speed	
Specifications	D-3-16
Performance Data	D-3-16
Dimensions	D-3-17
Product Numbers	D-3-20
Model Code	D-3-21

Typical Hydraulic Circuit


VIS 40 and 45 Series

Shuttle Valve, Two Way (Closed Center) —


Schematic Diagrams



Closed Loop Circuit



VIS 40 and 45 Motors Shuttle Flow Charts



- A**
4,5 bar [65 PSI] @ 60° C [140° F]
Δ Between Back-Pressure and Case Pressure (Typical Data)
- B**
15,2 bar [220 PSI] @ 60° C [140° F]
Δ Between Back-Pressure and Case Pressure (Typical Data)

Due to Machining Tolerances,
Flow May be More or Less


D-1

D-2

Typical Hydraulic Circuit

VIS 40 and
45 Series

Open Loop Circuit



Note:


Case pressure for VIS motors must not exceed 50 psi. With an "Open Loop Option" VIS motor, a case drain is not required, except if the return pressure is greater than 50 psi.

Typical Hydraulic Circuit


VIS 40 and

45 Series

Two-speed Circuit



Two-Speed Brake Motor Circuit




D-1

D-2

VIS 40 Series

Highlights



Description

The VIS 40 Series is the newest addition to the VIS product line. The VIS 40 is very close in size to the VIS 30, but with increased drive train strength, it has even greater torque capability. Maximum continuous output torque capability is rated to 2531 Nm [22,400 lb-in] with a displacement range from 505cc to 940cc per revolution. VIS 40 motors can be run up to 151 LPM [40 GPM] with pressure capability up to 310 bar (4500 PSI). The motor utilizes patented VIS technology with improved high-strength Geroler, optimized drive geometry, and two-piece pre-loaded balance plate for increased starting efficiency, reduced leakage and higher back pressure capacity. A wide variety of options are available including two-speed option, brake options and case flow options for both closed-loop and open loop applications.

Specifications

Geroler Element	8 Displacements
Flow l/min [GPM]	151 [40] Continuous 170 [45] Intermittent
Speed	Up to 454 RPM
Pressure bar [PSI]	310 [4500] Cont. 345 [5000] Inter. 380 [5500] Peak.
Torque Nm [lb - in]	2531 [22400] Cont. 3165 [28000] Inter.

Features

- Patented VIS Geroler technology
- Three moving components: (Geroler, star, drive, and output shaft)
- Maximized drive strength in compact package size
- Compact package size similar to VIS 30 Series.
- Two-piece pre-loaded pressure balance plate
- Variety of optional features including two-speed option, brake packages, and case flow solutions for both closed-loop and open-loop applications.

Benefits

- Extremely compact powerful package
- Increased torque capability
- Greatest horsepower density in the VIS motor line
- High efficiency
- Quiet, smooth operation
- Reliable, trouble-free performance
- Design Flexibility

Applications

- Skid Steer Loaders and Attachments
- Snow Removal Equipment
- Trenchers
- Grapples
- Rough Terrain Forklifts
- Wood Processing – Saw Mills & Chippers
- Metal Forming
- Entertainment / Amusement Rides
- Industrial Processing
- Harvesters



Skid Steer



Trencher




Digger



Port Equipment

VIS 40 Series

Specifications



SPECIFICATION DATA – VIS 40 MOTORS

Displ. cm ³ /r [in ³ /r]		325 [19.8]	400 [24.4]	505 [30.7]	570 [34.9]	630 [38.5]	685 [41.7]	785 [48.0]	940 [57.4]
Max. Speed (RPM) @ Flow	Continuous	440	357	279	244	221	204	177	148
	Intermittent	454	368	293	257	233	215	187	148
Flow l/min [GPM]	Continuous	151 [40]	151 [40]	151 [40]	151 [40]	151 [40]	151 [40]	151 [40]	151 [40]
	Intermittent	170 [45]	170 [45]	170 [45]	170 [45]	170 [45]	170 [45]	170 [45]	170 [45]
Torque Nm [lb - in]	Continuous	1445 [12789]	1781 [15760]	2240 [19829]	2531 [22400]	2531 [22400]	2531 [22400]	2531 [22400]	2531 [22400]
	Intermittent	1986 [17421]	1597 [14137]	2746 [21919]	2815 [24918]	3165 [28000]	3165 [28000]	3165 [28000]	3165 [28000]
Pressure Δ bar [Δ PSI]	Continuous	310 [4500]	310 [4500]	310 [4500]	279 [4040]	254 [3686]	235 [3389]	208 [3012]	171 [2489]
	Intermittent	345 [5000]	345 [5000]	345 [5000]	309 [4486]	315 [4574]	290 [4212]	254 [3682]	214 [3100]
	Peak	380 [5500]	380 [5500]	380 [5500]	380 [5500]	380 [5500]	380 [5500]	300 [4355]	250 [3621]
Weight kg [lb]	Standard or Wheel Mount	28,5 [62.9]	29,1 [64.2]	29,9 [66.0]	30,5 [67.2]	31,4 [68.2]	31,4 [69.2]	32,2 [71.0]	33,4 [73.6]
	Bearingless	16,3 [36.0]	16,9 [37.3]	17,7 [39.1]	18,3 [40.3]	18,7 [41.3]	19,2 [42.3]	20,0 [44.1]	21,2 [46.7]
Weight kg [lb]	Two-speed Standard or Wheel Mount	32,1 [70.8]	32,7 [72.1]	33,5 [73.9]	34,1 [75.1]	34,5 [76.1]	35,0 [77.1]	35,8 [78.9]	37,0 [81.5]
	Two-speed Bearingless	19,9 [43.9]	20,5 [45.2]	21,3 [47.0]	21,9 [48.2]	22,3 [49.2]	22,8 [50.2]	23,6 [52]	24,8 [54.6]

A simultaneous maximum torque and maximum speed NOT recommended.

Note:

To assure best motor life, run motor for approximately one hour at 30% of rated pressure before application to full load. Be sure motor is filled with fluid prior to any load applications.

Maximum Inlet Pressure:

400 bar [5800 PSI]
Do Not Exceed A Pressure Rating (for displacement size see chart above).

Return Pressure (Back-Pressure):

Minimum – 3,5 bar [50 PSI]
Maximum – 21 bar [300 PSI]

Note:

Return (back-pressure) must be 3,5 bar [50 PSI] greater than the case pressure, except with open loop circuit.

Δ Pressure:

The true Δ bar [ΔPSI] between inlet port and outlet port

Case Pressure:

Minimum – No Pressure
Maximum – 3,5 bar [50 PSI]

Note:

The case must be full when the motor is operating. A case drain is recommended.

Continuous Rating:

Motor may be run continuously at these ratings

Intermittent Operation:

10% of every minute

Peak Operation:

1% of every minute

Recommended Fluids:

Premium quality, anti-wear type hydraulic oil with a viscosity of not less than 70 SUS at operating temperature.

Recommended System Operating Temp.:

-34°C to 82°C [-30°F to 180°F]

Recommended Filtration:

Per ISO Cleanliness Code, 4406: 20/18/13

Shuttle:

Standard

Back-Pressure Relief Valve:

Required for closed loop circuit.

VIS 40 Series

Performance Data

Motors run with high efficiency in all areas designated with a number for torque and speed. For best motor life select a motor to run with a torque and speed range shown in the light shaded area.

Performance data is typical at 120 SUS. Actual data may vary slightly from unit to unit in production.

	Continuous
	Intermittent
	Will Operate at Reduced Life

325 cm³/r [19.8 in³/r]

Δ Pressure Bar [PSI]

Flow LPM [GPM]		250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275	4500 310	5000 345	5500 380
	4	668	1399	2834	4251	5583	6924	8258	9528	10387	11637	12659	
	15	75	158	320	480	631	782	933	1076	1174	1315	1430	
		46	46	46	44	43	43	42	42	39	37	36	
	8	680	1419	2867	4303	5711	7126	8530	9876	11269	12460	13782	14840
	30	77	160	324	486	645	805	964	1116	1273	1408	1557	1677
		93	91	90	87	85	84	83	81	78	74	70	66
	12	647	1412	2879	4340	5768	7195	8619	10010	11360	12672	14029	15246
	45	73	160	325	490	652	813	974	1131	1284	1432	1585	1723
		139	137	133	132	129	129	129	127	126	124	113	109
	16	690	1420	2852	4316	5741	7191	8621	10014	11412	12736	14081	15435
	61	78	160	322	488	649	812	974	1131	1289	1439	1591	1744
	186	184	181	179	174	170	168	168	166	161	154	151	
20	657	1250	2774	4407	5695	7170	8741	9952	11392	12789	14137	15339	
76	74	141	313	498	643	810	988	1124	1287	1445	1597	1733	
	233	229	226	223	217	214	211	209	208	203	200	197	
25	544	1266	2814	4154	5858	7220	8518	9936	11269	12654	14037	15334	
95	61	143	318	469	662	816	962	1123	1273	1430	1586	1732	
	291	287	283	280	277	269	266	264	260	256	254	248	
30	146	1177	2605	3968	5401	6882	8315	9678	11092	12536	13960	15321	
114	16	133	294	448	610	778	939	1094	1253	1416	1577	1731	
	341	345	340	336	333	325	323	320	316	312	307	303	
35	114	1144	2532	3960	5322	6768	8232	9589	11019	12228	13298	15023	
132	13	129	286	447	601	765	930	1083	1245	1382	1503	1697	
	396	402	396	392	387	378	377	372	369	363	353	354	
40	92	557	2047	3574	5032	6507	7944	9282	10687	12112	13439	14938	
151	10	63	231	404	569	735	898	1049	1207	1368	1518	1688	
	454	452	440	433	430	429	430	428	425	420	413	408	

400 cm³/r [24.4 in³/r]

Δ Pressure Bar [PSI]

Flow LPM [GPM]		250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275	4500 310	5000 345	5500 380
	4	823	1724	3493	5239	6880	8532	10177	11741	12800	14340	15600	
	15	93	195	395	592	777	964	1150	1327	1446	1620	1763	
		37	37	37	36	35	35	34	34	32	30	29	
	8	838	1749	3533	5302	7038	8781	10511	12171	13887	15354	16983	18288
		95	198	399	599	795	992	1188	1375	1569	1735	1919	2066
	30	75	74	73	71	69	68	67	66	63	60	57	53
	12	797	1740	3548	5349	7108	8866	10622	12335	13999	15616	17289	18788
		90	197	401	604	803	1002	1200	1394	1582	1764	1953	2123
	45	113	111	108	107	105	105	105	103	102	101	92	88
	16	850	1750	3515	5319	7074	8862	10624	12341	14063	15695	17353	19021
		96	198	397	601	799	1001	1200	1394	1589	1773	1961	2149
61	151	149	147	145	141	138	136	136	135	131	125	123	
20	810	1540	3419	5431	7018	8836	10771	12264	14039	15760	17421	18902	
	92	174	386	614	793	998	1217	1386	1586	1781	1968	2136	
76	189	186	183	181	176	174	171	170	169	165	163	160	
25	670	1560	3467	5118	7219	8897	10497	12244	13887	15594	17299	18896	
	76	176	392	578	816	1005	1186	1383	1569	1762	1954	2135	
95	236	233	230	227	225	218	216	215	211	208	206	202	
30	180	1450	3210	4890	6656	8480	10246	11927	13669	15448	17203	18881	
	20	164	363	552	752	958	1158	1348	1544	1745	1944	2133	
114	277	280	276	273	270	264	262	259	256	253	250	246	
35	140	1410	3120	4880	6559	8341	10144	11817	13579	15068	16388	18514	
	16	159	353	551	741	942	1146	1335	1534	1702	1852	2092	
132	321	326	321	318	314	307	306	302	299	295	287	287	
40	113	687	2522	4405	6201	8019	9789	11438	13170	14926	16561	18409	
	13	78	285	498	701	906	1106	1292	1488	1686	1871	2080	
151	368	367	357	352	349	348	349	347	345	341	335	331	

6201 } Torque [lb-in]
701 } Nm
349 } Speed RPM

VIS 40 Series

Performance Data

Motors run with high efficiency in all areas designated with a number for torque and speed. For best motor life select a motor to run with a torque and speed range shown in the light shaded area.

Performance data is typical at 120 SUS. Actual data may vary slightly from unit to unit in production.

	Continuous
	Intermittent
	Will Operate at Reduced Life

505 cm³/r [30.7 in³/r]


Δ Pressure Bar [PSI]

	250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275	4500 310	5000 345	5500 380
4	1035	2169	4395	6592	8656	10735	12804	14773	16105	18043	19628	
15	117	245	497	745	978	1213	1447	1669	1820	2039	2218	
8	1055	2200	4445	6671	8855	11049	13225	15313	17473	19319	21368	23010
30	119	249	502	754	1000	1248	1494	1730	1974	2183	2414	2600
12	1003	2190	4464	6730	8944	11155	13364	15520	17614	19648	21753	23640
45	113	247	504	760	1011	1260	1510	1754	1990	2220	2458	2671
16	1069	2202	4422	6692	8901	11150	13367	15527	17694	19747	21833	23932
61	121	249	500	756	1006	1260	1510	1754	1999	2231	2467	2704
20	1019	1938	4301	6833	8830	11117	13552	15431	17663	19829	21919	23783
76	115	219	486	772	998	1256	1531	1743	1996	2240	2476	2687
25	843	1963	4363	6440	9083	11194	13207	15406	17473	19620	21765	23775
95	95	222	493	728	1026	1265	1492	1741	1974	2217	2459	2686
30	226	1824	4039	6153	8375	10670	12892	15006	17199	19437	21645	23756
114	26	206	456	695	946	1206	1457	1695	1943	2196	2446	2684
35	176	1774	3926	6140	8252	10494	12763	14868	17086	18959	20619	23294
132	20	200	444	694	932	1186	1442	1680	1930	2142	2330	2632
40	142	864	3174	5542	7803	10089	12317	14391	16570	18779	20837	23162
151	16	98	359	626	882	1140	1392	1626	1872	2122	2354	2617
	293	292	284	279	277	277	277	276	274	271	267	263

570cm³/r [34.9 in³/r]

Δ Pressure Bar [PSI]

	250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275	4500 310	5000 345	5500 380
4	1177	2466	4996	7494	9841	12204	14556	16794	18308	20511	22313	
15	133	279	564	847	1112	1379	1645	1897	2069	2317	2521	
8	1199	2501	5053	7584	10067	12560	15034	17408	19864	21962	24292	26158
30	135	283	571	857	1137	1419	1699	1967	2244	2481	2745	2955
12	1140	2489	5074	7650	10167	12681	15193	17644	20024	22336	24729	26874
45	129	281	573	864	1149	1433	1717	1993	2262	2524	2794	3036
16	1216	2503	5027	7608	10119	12675	15195	17652	20115	22449	24820	27206
61	137	283	568	860	1143	1432	1717	1994	2273	2536	2804	3074
20	1159	2203	4890	7768	10038	12638	15407	17542	20080	22542	24918	27037
76	131	249	552	878	1134	1428	1741	1982	2269	2547	2815	3055
25	958	2231	4960	7321	10325	12725	15014	17513	19863	22305	24743	27027
95	108	252	560	827	1167	1438	1696	1979	2244	2520	2796	3054
30	257	2074	4591	6994	9520	12130	14656	17059	19552	22096	24606	27006
114	29	234	519	790	1076	1370	1656	1927	2209	2496	2780	3051
35	200	2017	4463	6980	9381	11930	14509	16902	19423	21553	23440	26481
132	23	228	504	789	1060	1348	1639	1910	2195	2435	2648	2932
40	162	983	3608	6300	8870	11469	14002	16360	18837	21348	23688	2633
151	18	111	408	712	1002	1296	1582	1848	2128	2412	2676	2975
	257	257	249	246	244	243	244	243	241	238	234	232



VIS 40 Series

630 cm³/r [38.5 in³/r]

Δ Pressure Bar [PSI]

Performance Data

Motors run with high efficiency in all areas designated with a number for torque and speed. For best motor life select a motor to run with a torque and speed range shown in the light shaded area.

Performance data is typical at 120 SUS. Actual data may vary slightly from unit to unit in production.

	Continuous
	Intermittent
	Will Operate at Reduced Life

	250	500	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500
	15	35	70	105	140	170	205	240	275	310	345	380
4	1298	2720	5511	8267	10856	13463	16058	18526	20197	22627	24615	
	147	307	623	934	1227	1521	1814	2093	2282	2556	2781	
15	23	23	23	23	22	22	22	22	20	19	18	
8	1323	2759	5575	8366	11105	13856	16585	19204	21913	24227	26797	28856
	149	312	630	945	1255	1565	1874	2170	2476	2737	3028	3260
30	48	47	46	45	44	43	42	42	40	38	36	34
12	1257	2746	5598	8439	11216	13990	16760	19464	22089	24640	27279	29646
	142	310	632	954	1267	1581	1894	2199	2496	2784	3082	3350
45	72	70	68	68	67	67	67	65	65	64	58	56
16	1341	2761	5546	8393	11163	13982	16763	19472	22190	24765	27381	30012
	152	312	627	948	1261	1580	1894	2200	2507	2798	3094	3391
61	96	94	93	92	89	87	86	86	86	83	79	78
20	1278	2430	5394	8569	11073	13942	16996	19352	22151	24867	27488	29825
	144	275	609	968	1251	1575	1920	2186	2503	2810	3106	3370
76	120	118	116	115	112	110	108	108	107	104	103	102
25	1057	2461	5471	8076	11390	14038	16563	19320	21912	24605	27295	29815
	119	278	618	912	1287	1586	1871	2183	2476	2780	3084	3369
95	150	148	146	144	143	138	137	136	134	132	130	128
30	283	2288	5065	7716	10502	13381	16167	18819	21569	24375	27145	29792
	32	258	572	872	1187	1512	1827	2126	2437	2754	3067	3366
114	175	175	175	173	171	167	166	164	163	160	158	156
35	221	2225	4923	7700	10349	13160	16006	18646	21427	23776	25858	29212
	25	251	556	870	1169	1487	1808	2107	2421	2686	2922	3301
132	204	207	203	202	199	194	194	191	190	187	182	182
40	178	1084	3980	6950	9785	12652	15446	18048	20780	23551	26132	29047
	20	122	450	785	1106	1430	1745	2039	2348	2661	2952	3282
151	233	233	226	223	221	221	221	220	219	216	213	210

685 cm³/r [41.7 in³/r]

Δ Pressure Bar [PSI]

	250	500	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500
	15	35	70	105	140	170	205	240	275	310	345	380
4	1406	2947	5969	8954	11758	14582	17392	20066	21875	24507	26661	
	159	333	674	1012	1328	1647	1965	2267	2472	2769	3012	
15	22	22	22	21	20	20	20	20	19	18	17	
8	1433	2989	6038	9062	12028	15007	17964	20800	23734	26241	29025	31254
	162	338	682	1024	1359	1696	2030	2350	2682	2965	3279	3531
30	44	43	43	42	40	40	39	39	37	35	33	31
12	1362	2974	6063	9141	12148	15152	18153	21082	23925	26688	29547	32110
	154	336	685	1033	1373	1712	2051	2382	2703	3015	3338	3628
45	66	65	63	63	61	61	61	60	60	59	54	52
16	1453	2991	6007	9090	12090	15145	18156	21091	24034	26823	29656	32506
	164	338	679	1027	1366	1711	2051	2383	2715	3031	3351	3673
61	88	87	86	85	83	81	80	80	79	77	73	72
20	1384	2632	5842	9281	11994	15100	18408	20960	23992	26934	29773	32304
	156	297	660	1049	1355	1706	2080	2368	2711	3043	3364	3650
76	111	109	107	106	103	102	100	99	99	96	95	94
25	1145	2666	5926	8748	12337	15205	17939	20926	23733	26650	29563	32293
	129	301	670	988	1394	1718	2027	2364	2681	3011	3340	3649
95	138	136	135	133	132	128	126	126	124	122	120	118
30	307	2478	5486	8357	11375	14493	17511	20383	23361	26401	29401	32268
	35	280	620	944	1285	1637	1978	2303	2639	2983	3322	3646
114	162	164	161	160	158	154	153	152	150	148	146	144
35	239	2410	5332	8340	11209	14254	17337	20196	23207	25752	28007	31640
	27	272	602	942	1266	1610	1959	2282	2622	2910	3164	3575
132	188	191	188	186	184	179	179	177	175	172	168	168
40	193	1174	4311	7527	10598	13704	16730	19548	22507	25508	28304	31461
	22	133	487	850	1197	1548	1890	2209	2543	2882	3198	3555
151	215	215	209	206	204	204	204	203	202	199	196	194

10598 } Torque [lb-in]
1197 } Nm
204 } Speed RPM

VIS 40 Series

Performance Data

Motors run with high efficiency in all areas designated with a number for torque and speed. For best motor life select a motor to run with a torque and speed range shown in the light shaded area.

Performance data is typical at 120 SUS. Actual data may vary slightly from unit to unit in production.

Continuous

Intermittent

Will Operate at Reduced Life

785 cm³/r [48.0 in³/r]
Δ Pressure Bar [PSI]

Flow LPM [GPM]		250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275	4500 310	5000 345
	4	1618	3392	6871	10306	13535	16784	20020	23097	25180	28210	30689
	15	183 19	383 19	776 19	1164 18	1529 18	1896 18	2262 17	2610 17	2845 16	3187 15	3467 15
	8	1649	3440	6950	10431	13845	17275	20678	23942	27320	30205	33410
	30	186 38	389 38	785 37	1178 36	1564 35	1952 35	2336 34	2705 34	3087 32	3413 31	3775 29
	12	1568	3423	6979	10522	13984	17441	20895	24267	27540	30720	34011
	45	177 57	387 56	789 55	1189 54	1580 53	1971 53	2361 53	2742 52	3112 52	3471 51	3843 47
	16	1672	3443	6914	10464	13917	17433	20899	24277	27665	30876	34137
	61	189 77	389 76	781 75	1182 74	1572 72	1970 70	2361 69	2743 69	3126 69	3488 67	3857 64
	20	1593	3030	6725	10683	13805	17382	21190	24127	27617	31003	34271
76	180 96	342 95	760 93	1207 92	1560 89	1964 88	2394 87	2726 86	3120 86	3503 84	3872 83	
25	1318	3069	6821	10069	14201	17502	20649	24087	27319	30677	34030	
95	149 120	347 118	771 117	1138 115	1604 114	1977 111	2333 110	2721 109	3087 107	3466 106	3845 105	
30	353	2852	6315	9620	13094	16683	20157	23463	26891	30390	33843	
114	40 141	322 142	713 140	1087 139	1479 137	1885 134	2277 133	2651 132	3038 130	3434 129	3824 127	
35	275	2774	6138	9600	12903	16408	19956	23247	26714	29643	32238	
132	31 163	313 166	693 163	1085 162	1458 160	1854 156	2255 155	2627 154	3018 152	3349 150	3642 146	
40	222	1351	4962	8665	12200	15774	19257	22501	25908	29362	32580	
151	25 187	153 187	561 181	979 179	1378 177	1782 177	2176 177	2542 177	2927 175	3317 173	3681 170	

940 cm³/r [57.4 in³/r]
Δ Pressure Bar [PSI]


Flow LPM [GPM]		250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275
	4	1935	4056	8216	12325	16185	20071	23940	27620	30111
	15	219 16	458 16	928 16	1393 15	1829 15	2268 15	2705 14	3121 14	3402 14
	8	1972	4114	8311	12473	16557	20658	24727	28631	32670
		223	465	939	1409	1871	2334	2794	3235	3691
	30	32	31	31	30	29	29	28	28	27
	12	1875	4094	8346	12582	16722	20857	24987	29019	32933
		212	463	943	1422	1889	2357	2823	3279	3721
	45	48	47	46	45	45	45	45	44	43
	16	2000	4117	8268	12513	16642	20846	24992	29032	33083
	226	465	934	1414	1880	2355	2824	3280	3738	
61	64	63	62	62	60	59	58	58	57	
20	1905	3623	8042	12776	16509	20786	25339	28851	33025	
	215	409	909	1443	1865	2348	2863	3260	3731	
76	80	79	78	77	75	74	73	72	72	
25	1576	3670	8157	12041	16982	20929	24693	28804	32669	
	178	415	922	1360	1919	2365	2790	3254	3691	
95	100	99	98	96	96	93	92	91	90	
30	423	3411	7551	11504	15658	19950	24104	28057	32157	
	48	385	853	1300	1769	2254	2723	3170	3633	
114	118	119	117	116	115	112	111	110	109	
35	329	3317	7340	11480	15429	19621	23864	27799	31945	
	37	375	829	1297	1743	2217	2696	3141	3609	
132	137	139	136	135	133	130	130	128	127	
40	266	1616	5934	10361	14589	18863	23029	26907	30982	
	30	183	670	1171	1648	2131	2602	3040	3500	
151	156	156	152	149	148	148	148	148	147	

5934 } Torque [lb-in]
670 } Nm
152 } Speed RPM

VIS 40 Series

Dimensions

Standard and Wheel Mount
— SAE



Ports




1—1/16-12 UN-2B SAE O-ring Ports (2)
9/16-18 UNF-2B SAE O-ring Case Drain Port (1)

Standard Rotation Viewed from Shaft End

Port A Pressurized — CW

Port B Pressurized — CCW



Standard Motors (SAE)



STANDARD MOTORS (SAE)

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]
325 [19.8]	223,5 [8.80]	195,3 [7.69]
400 [24.4]	230,4 [9.07]	201,9 [7.95]
505 [30.7]	239,3 [9.42]	211,1 [8.31]
570 [34.9]	245,4 [9.66]	217,2 [8.55]
630 [38.5]	250,7 [9.87]	222,5 [8.76]
685 [41.7]	255,3 [10.05]	227,1 [8.94]
785 [48.0]	264,7 [10.42]	236,2 [9.30]
940 [57.4]	278,4 [10.96]	249,9 [9.84]

Wheel Motors (SAE)




WHEEL MOTORS (SAE)

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]
325 [19.8]	138,7 [5.46]	110,5 [4.35]
400 [24.4]	145,5 [5.73]	117,1 [4.61]
505 [30.7]	154,4 [6.08]	126,2 [4.97]
570 [34.9]	160,5 [6.32]	132,3 [5.21]
630 [38.5]	165,9 [6.53]	137,7 [5.42]
685 [41.7]	170,4 [6.71]	142,2 [5.60]
785 [48.0]	179,8 [7.08]	151,4 [5.96]
940 [57.4]	193,5 [7.62]	165,1 [6.50]

VIS 40 Series

Dimensions

Oversize Flange
224,0 [8.82] B.C.




Ports

- 1-1/16-12 UN-2B SAE O-ring Ports (2)
- 9/16-18 UNF-2B SAE O-ring Case Drain Port (1)

Standard Rotation Viewed from Shaft End

- Port A Pressurized — CW
- Port B Pressurized — CCW



STANDARD MOTORS (OVERSIZE)



Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]
325 [19.8]	196,6 [7.74]	168,1 [6.62]
400 [24.4]	203,2 [8.00]	175,0 [6.89]
505 [30.7]	181,4 [8.36]	183,9 [7.24]
570 [34.9]	187,4 [8.60]	190,2 [7.49]
630 [38.5]	192,5 [8.81]	195,3 [7.69]
685 [41.7]	197,6 [8.99]	199,9 [7.87]
785 [48.0]	206,8 [9.35]	209,3 [8.24]
940 [57.4]	220,5 [9.89]	223,0 [8.78]

VIS 40 Series

Dimensions

Standard and Wheel Mount
– ISO



Standard Motors (ISO)



STANDARD MOTORS (ISO)

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]
325 [19.8]	211,6 [8.33]	183,1 [7.21]
400 [24.4]	218,2 [8.59]	190,0 [7.48]
505 [30.7]	227,3 [8.95]	198,9 [7.83]
570 [34.9]	233,4 [9.19]	205,2 [8.08]
630 [38.5]	238,8 [9.40]	210,3 [8.28]
685 [41.7]	243,3 [9.58]	214,9 [8.46]
785 [48.0]	252,5 [9.94]	224,3 [8.83]
940 [57.4]	266,2 [10.48]	238,0 [9.37]

Wheel Motors (ISO)




WHEEL MOTORS (ISO)

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]
325 [19.8]	137,4 [5.41]	109,0 [4.29]
400 [24.4]	144,0 [5.67]	115,8 [4.56]
505 [30.7]	153,2 [6.03]	124,7 [4.91]
570 [34.9]	159,3 [6.27]	131,1 [5.16]
630 [38.5]	164,6 [6.48]	136,1 [5.36]
685 [41.7]	169,2 [6.66]	140,7 [5.54]
785 [48.0]	178,3 [7.02]	150,1 [5.91]
940 [57.4]	192,0 [7.56]	163,8 [6.45]

VIS 40 Series

Dimensions

Bearingless



Ports

1-1/16-12 UN-2B SAE O-ring Ports (2)

9/16-18 UNF-2B SAE O-ring Case Drain Port (1)

Or



G 3/4 (BSP) O-ring Ports (2)

G 1/4 (BSP) O-ring Case Drain Port (1)

Standard Rotation Viewed from Drive End

Port A Pressurized — CW

Port B Pressurized — CCW




For VIS 40 bearingless motor application information, contact your Eaton representative (mating coupling blanks available from Eaton Hydraulics).

C	59,94	[2.36]	Dia.
D	49,00	[1.93]	Dia.
E	155,86	[6.14]	Max.
F	150,88	[5.94]	Min.
			Full Form Dia.
G	26,92	[1.06]	
H	33,30	[1.21]	
J	106,43	[4.19]	
			Full Form Dia.
K	72,64	[2.86]	
L	15		


Note:

After machining blank, part must be hardened per Eaton specification.



BEARINGLESS MOTORS

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]
325 [19.8]	141,2 [5.56]	113,3 [4.46]
400 [24.4]	148,1 [5.83]	120,1 [4.73]
505 [30.7]	157,2 [6.19]	129,0 [5.08]
570 [34.9]	163,3 [6.43]	135,1 [5.32]
630 [38.5]	168,4 [6.63]	140,5 [5.53]
685 [41.7]	173,2 [6.82]	145,3 [5.72]
785 [48.0]	182,2 [7.18]	154,4 [6.08]
940 [57.4]	196,1 [7.72]	168,1 [6.62]





VIS 40 Series

Installation Information

Bearingless

- 1 Internal spline in mating part to be per spline data. Specification material to be ASTM A304, 8620H carburize to a hardness of 60-64 HRC with case depth (to 50HRC) of 0,076 -1,27 [.030 -.050]. Dimensions apply after heat treat.
- 2 Mating part to have critical dimensions as shown. Oil holes must be provided and open for proper oil circulation.
- 3 Seal to be furnished with motor for proper oil circulation thru splines.
- 4 Similar to SAE "C" Four Bolt Flange.




Spline Pitch.....	10/20
Pressure Angle.....	30°
Number of teeth.....	16
Class of Fit.....	Ref. 5
Type of Fit.....	Side
Pitch Diameter.....	Ref. 40,640000 [1.6000000] H H
Base Diameter.....	Ref. 35,195272 [1.3856406]
Major Diameter.....	43,56 [1.715] Max. 43,18 [1.700]
Min. Minor Diameter.....	36,83 -37,08 [1.450 -1.460]
Form Diameter, Min.....	42,47 [1.672]
Fillet Radius.....	0,64 -0,76 [.025 -.030]
Tip Radius.....	0,25 -0,51 [.010 -.020]
Finish.....	1,6 (63)
Involute Profile Variation.....	+0,000 -0,025 [+0.0000 -.0010]
Total Index Variation.....	0,040 [.0016]
Lead Variation.....	0,013 [.0005]
Circular Space Width:	
Maximum Actual.....	4,105 [.1616]
Minimum Effective.....	3,995 [.1573]
Maximum Effective.....	Ref. 4,056 [.1597]
Minimum Actual.....	Ref. 4,081 [.1582]
Dimension Between Two Pins.....	Ref. 34,272 -34,450 [1.3493 -1.3563]
Pin Diameter.....	4,389 [.1728]

VIS 40 Series

Dimensions Shafts

SAE


40 mm Straight




Note:

For motor torque ratings above 875 Nm [7750 lb - in] use split coupler.

1-1/2 Inch 17 Tooth Splined



1-3/4 Inch Tapered



VIS 40 Series

Side Load Capacity

SAE



These curves indicate the radial load capacity on the motor shaft(s) at various locations.

The curve is based on B 10 bearing life (2000 hours of 12,000,000 shaft revolutions at 100 RPM) at rated output torque.

To determine radial load at speeds other than 100 RPM, multiply the load values given on the bearing curve by the factors in the chart below.

RPM	Multiplication Factor
50	1.23
100	1.00
200	0.81
300	0.72
400	0.66
500	0.62
600	0.58
700	0.56
800	0.54

For 3,000,000 shaft revolutions or 500 hours — Increase these shaft loads 52%.




VIS 40 Series

Dimensions Shafts

Oversize Flange
224,0 [8.82] B.C.


40 mm Straight




Note:

For motor torque ratings above 875 Nm [7750 lb - in] use split coupler.

46 mm 28 Tooth Splined



1-3/4 Inch Tapered



VIS 40 Series

Side Load Capacity

Oversize Flange
224,0 [8.82] B.C.


These curves indicate the radial load capacity on the motor shaft(s) at various locations.

The curve is based on B 10 bearing life (2000 hours of 12,000,000 shaft revolutions at 100 RPM) at rated output torque.

To determine radial load at speeds other than 100 RPM, multiply the load values given on the bearing curve by the factors in the chart below.

RPM	Multiplication Factor
50	1.23
100	1.00
200	0.81
300	0.72
400	0.66
500	0.62
600	0.58
700	0.56
800	0.54

For 3,000,000 shaft revolutions or 500 hours — Increase these shaft loads 52%.




VIS 40 Series

Dimensions

Shafts

ISO


40 mm Straight




Note:

For motor torque ratings above 875 Nm [7750 lb - in] use split coupler.

38,1 mm [1-1/2 inch] 17 Tooth Splined



45 mm Tapered



VIS 40 Series

Side Load Capacity

ISO



These curves indicate the radial load capacity on the motor shaft(s) at various locations.

The curve is based on B 10 bearing life (2000 hours of 12,000,000 shaft revolutions at 100 RPM) at rated output torque.

To determine radial load at speeds other than 100 RPM, multiply the load values given on the bearing curve by the factors in the chart below.

RPM	Multiplication Factor
50	1.23
100	1.00
200	0.81
300	0.72
400	0.66
500	0.62
600	0.58
700	0.56
800	0.54

For 3,000,000 shaft revolutions or 500 hours — Increase these shaft loads 52%.



VIS 40 Series

Product Numbers

Closed Loop

Use digit prefix —
168-, 177-, or 180- plus four
digit number from charts for
complete product number—
Example: 168-0018.

**Orders will not be accepted
without three digit prefix.**

SAE

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r [in ³ /r] / PRODUCT NUMBER							
			325 [19.8]	400 [24.4]	505 [30.7]	570 [34.9]	630 [38.5]	685 [41.7]	785 [48.0]	940 [57.4]
Standard	40 mm Straight	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	177-0220	-0218	-0032	-0022	-0033	-0034	-0035	-0036
	1 1/2 inch 17 Tooth Splined	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	177-0221	—	-0024	-0026	-0037	-0038	-0039	-0040
	1 3/4 inch Tapered	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	-0041	-0042	-0043	-0044	-0045	-0046
Wheel	40 mm Straight	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	-0007	-0008	-0009	-0010	-0011	-0012
	1 1/2 inch 17 Tooth Splined	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	-0013	-0014	-0015	-0016	-0017	-0018
	1 3/4 inch Tapered	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	180-0088	-0019	-0020	-0021	-0022	-0023	-0024
Bearingless		1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	-0015	-0016	-0017	-0018	-0019	-0020

168-0018

Oversize

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r [in ³ /r] / PRODUCT NUMBER							
			325 [19.8]	400 [24.4]	505 [30.7]	570 [34.9]	630 [38.5]	685 [41.7]	785 [48.0]	940 [57.4]
Standard	40 mm Straight	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	177-0047	-0048	—	—	—	—
	46 mm 28 Tooth Splined	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	177-0053	-0054	—	—	—	—
	1 3/4 inch Tapered	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	177-0059	-0060	—	—	—	—

ISO

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r [in ³ /r] / PRODUCT NUMBER							
			325 [19.8]	400 [24.4]	505 [30.7]	570 [34.9]	630 [38.5]	685 [41.7]	785 [48.0]	940 [57.4]
Standard	40 mm Straight	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0065	-0066	-0067	-0068	-0069	-0070
	45 mm Tapered	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	177-0223	-0224	-0071	-0072	-0073	-0074	-0075	-0076
	1 1/2 inch 17 Tooth Splined	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0077	-0078	-0079	-0080	-0081	-0082
Wheel	40 mm Straight	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0025	-0026	-0027	-0028	-0029	-0030
	45 mm Tapered	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0031	-0032	-0033	-0034	-0035	-0036
	1 1/2 inch 17 Tooth Splined	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0037	-0038	-0039	-0040	-0041	-0042
Bearingless		G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0021	-0022	-0023	-0024	-0025	-0026

168-0024

Note:


The product numbers on this page are for motors used in closed loop circuits. They include a back-pressure relief valve that is set at 4,5 bar [65 PSI].

- A case drain is required for all closed loop VIS motor applications.
- The maximum case pressure for the VIS motor is 3,5 bar [50 PSI].

VIS 40 Series

Model Code

The following 16 - digit coding system has been developed to identify all of the configuration options for the VIS 40 motor. Use this model code to specify a motor with the desired features. All 16 digits of the code must be present when ordering. You may want to photocopy the matrix below to ensure that each number is entered in the correct box.



1, 2, 3 Product Series

ADL – VIS 40 Motor

4, 5 Displacement cm³/r [in³/r]

20 – 325 [19.8]

24 – 400 [24.4]

31 – 505 [30.7]

35 – 570 [34.9]

38 – 630 [38.5]

42 – 685 [41.7]

48 – 785 [48.0]

57 – 940 [57.4]

6 Mounting Type

A – 4 Bolt Bearingless
127,00 [5.000] Pilot Dia. with
12,19 [.480] Pilot Length
and 14,35 [.565] Dia holes
on 161,92 [6.375] Dia. Bolt
Circle

B – 4 Bolt Wheel Mount
160,00 [6.3] Pilot Dia. With
5,8 [.23] Pilot Length and
18,00 [.709] Dia. Holes on
200,00 [7.874] Dia. Bolt
Circle (ISO Compatible)

C – 4 Bolt Oversize Flange
185,4 [7.30] Rear Pilot Dia.,
169,90 [6.689], 139,93
[5.509], 127,0 [5.00] Dia
(Front Pilots) and 18,01
[.709] Dia. Holes on 224,00
[8.819] Dia. Bolt Circle

F – 4 Bolt Standard Mount
(SAE CC) 127,00 [5.000] Pilot
Dia. With 12,2 [.48] Pilot
Length and 14,32 [.564] Dia.
Holes on 161,92 [6.375] Dia.
Bolt Circle

G – 4 Bolt Wheel Mount
139,7 [5.50] Pilot Dia. with
7,9 [.31] Pilot Length and
14,32 [.564] Dia. Holes on
184,15 [7.250] Dia. Bolt
Circle (SAE Compatible)

H – 4 Bolt Standard Mount
125,00 [4.92] Pilot Dia. with
8,9 [.35] Pilot Length and
14,00 [.551] Dia. Holes on

160,00 [6.299] Dia. Bolt
Circle (ISO Compatible)

M – Standard, 4 Bolt: 169,75
[6.683] Pilot Dia. with 4,3
[.17] Pilot Length and M16
X 2 -6H Threaded Holes
on 224,00 [8.819] Dia. Bolt
Circle (To be selected for
Brake Option)

7, 8 Output Shaft

00 – None (Bearingless)

01 – 45 mm Dia. 10:1
Tapered Shaft Per ISO R775
with M30 x 2- 6H Threaded
Shaft End, 12W x 8H x 28L
[.472W x .313H x 1.102L]
Key

02 – 1-3/4 inch Dia. .125:1
Tapered Shaft Per SAE J 501
with 1 1/4 - 18 UNEF - 2A
Threaded Shaft End, 11,11
[.4375] Square x 31,8 [1.25]
Straight Key

04 – 46 mm Dia. Flat Root
Side Fit, 28 Tooth, 16/32 DP
30 Degree Involute Spline,
93,0 [3.66] Minimum Full
Spline with M16 X 2,0-6H
Thread in End

07 – 40 mm Dia. Straight
Shaft with M12 x 1,75 -
6H Thread in End, 12W
x 8H x 63L [.472W x
.313H x 2.480L] Key (SAE
Compatible)

08 – 1-1/2 inch Dia. Flat
Root Side Fit, 17 Tooth,
12/24 DP 30 Degree Involute
Spline, 39,1 [1.54] Minimum
Full Spline with 3/8-16 UNC
- 2B Thread in End (SAE
Compatible)

09 – 1-1/2 inch Dia. Flat
Root Side Fit, 17 Tooth,
12/24 DP 30 Degree Involute
Spline, 56,6 [2.23] Minimum
Full Spline with M12 x 1.75
- 6H Thread in End (ISO
Compatible)

10 – 40 mm Dia. Straight
Shaft with M12 x 1,75 -
6H Thread in End, 12W
x 8H x 67L [.472W x
.313H x 2.630L] Key (ISO
Compatible)

9 Ports

A – 1-1/16-12 UN-2B Size 12
O-ring Port, Accepts Fittings
for SAE J1926

B – G 3/4 (BSP) Straight
Thread Port

10 Case Flow Options

A – Shuttle Valve with
9/16-18 UNF-2B, Size 6 O-ring
Port Case Drain, Accepts
Fittings for SAE J1926

B – Shuttle Valve with G 1/4
(BSP) Straight Thread Port
Case Drain

C – Check valve with
leakage orifice, no case
drain (for Open Loop only)

11 Back-Pressure Relief

0 – None (for Open Loop
Only)

1 – Set at 4,5 bar [65 PSI]
(for Manual Pumps)

2 – Set at 15,2 bar [220 PSI]
(for Servo Pumps)

4 – Set at 15,2 bar [300 PSI]
(for high charge Servo
Pumps)

12, 13 Special Features

00 – None

08 – Spring Applied
Hydraulic Release Wet Brake
with Brake Capacity of
20,000 lbf-in Static and 150
lbf/in² release pressure

14 Paint/ Special Packaging

0 – Primer, Individual Box

A – Low Gloss Black Primer,
Individual Box

B – No Paint, Bulk Box
Option

C – Low Gloss Black Primer,
Bulk Box Option

15 Eaton Assigned Code when Applicable


0 – Assigned Code

16 Eaton Assigned Design Code

D – Assigned Design Code

VIS 40 Series Two-speed

Specifications



VIS 40 Series motors are available with an integral two-speed feature that allows the operator to shift the motor between low speed high torque (LSHT) mode and high speed low torque (HSLT) mode.

In the LSHT mode, output torque and rotation speed values are equal to those of the conventional VIS 40 motor. In the HSLT mode motor displacement is reduced by one third, resulting in a fifty percent increase in rotation speed and a torque output reduction of one third.

The VIS 40 two-speed motor is bidirectional. It will function with equal shaft output in either rotation

direction (CW or CCW) in both LSHT and HSLT modes. Shift on the fly technology allows full-power operation throughout the full duration of the shift.

Changing between modes is accomplished by changing the displacement in a ratio of 1 to 1.5. An external two-position three-way control valve is required for shifting pressure to the pilot port between low pressure (LSHT mode) and pilot signal pressure (HSLT mode).

An integral selector valve shifts the motor from LSHT mode to HSLT mode. Initially, low pressure is supplied to the pilot port. The selector valve is biased to LSHT mode by a return spring. When pilot signal pressure is supplied to the

pilot port and 3,5 Δbar [50 PSI] is reached, the selector valve overcomes return spring force and shifts the spool to select HSLT mode.

Oil on the opposite side of the spool is drained to tank via the drain port. The pressure difference between the pilot port and drain port must be maintained to keep the motor in the high speed mode. When pilot pressure is removed from the pilot port, the pressure in the pilot end of the spool valve is relieved and drained back through the control valve and the return spring forces the spool valve to LSHT position.

Pilot pressure may come from any source that will provide uninterrupted pressure during the high-speed mode operation. Allowable pilot pressure must be at least 3,5 Δbar [50 PSI] and may be as high as full operating pressure of the motor.

All VIS 40 Series two-speed motors are equipped with a return line shuttle for closed circuit applications as standard equipment. All options available on the conventional VIS 40 are also available on VIS 40 two-speed motors.

Performance Data


In the LSHT mode, torque and speed values are equal to those of the conventional VIS 40 motor. In the HSLT mode, rotation speed is increased by fifty percent and torque output is reduced by one third. The VIS 40 two-speed motor will function with equal shaft output in either rotation direction (CW or CCW) in both LSHT and HSLT modes.

VIS 40 Series



Two-speed

Dimensions

Standard and Wheel Mount
– SAE





Standard Motors (SAE)



STANDARD MOTORS (SAE)

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
325 [19.8]	259,3 [10.21]	231,4 [9.11]	186,2 [7.33]
400 [24.4]	265,9 [10.47]	238,0 [9.37]	193,0 [7.60]
505 [30.7]	275,1 [10.83]	246,9 [9.72]	201,7 [7.94]
570 [34.9]	281,2 [11.07]	253,0 [9.96]	208,0 [8.19]
630 [38.5]	286,3 [11.27]	258,3 [10.17]	213,4 [8.40]
685 [41.7]	290,8 [11.45]	262,9 [10.35]	217,7 [8.57]
785 [48.0]	300,2 [11.82]	272,3 [10.72]	227,3 [8.95]
940 [57.4]	313,9 [12.36]	286,0 [11.26]	241,0 [9.49]

Wheel Motors (SAE)



WHEEL MOTORS (SAE)



Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
325 [19.8]	174,5 [6.87]	146,6 [5.77]	101,3 [3.99]
400 [24.4]	181,1 [7.13]	153,2 [6.03]	108,2 [4.26]
505 [30.7]	190,2 [7.49]	162,1 [6.38]	116,8 [4.60]
570 [34.9]	196,3 [7.73]	168,1 [6.62]	123,2 [4.85]
630 [38.5]	201,4 [7.93]	173,5 [6.83]	128,5 [5.06]
685 [41.7]	206,0 [8.11]	178,1 [7.01]	132,8 [5.23]
785 [48.0]	215,4 [8.48]	187,5 [7.38]	142,5 [5.61]
940 [57.4]	229,1 [9.02]	201,2 [7.92]	156,2 [6.15]

VIS 40 Series

Two-speed

Dimensions

Oversize Flange
224,0 [8.82] B.C.



OVERSIZE MOTORS


Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
325 [19.8]	232,4 [9.15]	204,0 [8.03]	159,0 [6.26]
400 [24.4]	239,3 [9.42]	210,6 [8.29]	165,6 [6.52]
505 [30.7]	248,2 [9.77]	220,0 [8.66]	174,8 [6.88]
570 [34.9]	254,3 [10.01]	226,1 [8.90]	181,1 [7.13]
630 [38.5]	259,3 [10.21]	231,4 [9.11]	186,4 [7.34]
685 [41.7]	263,9 [10.39]	236,0 [9.29]	190,8 [7.51]
785 [48.0]	273,1 [10.75]	245,1 [9.65]	200,2 [7.88]
940 [57.4]	286,8 [11.29]	258,8 [10.19]	213,9 [8.42]

VIS 40 Series

Two-speed

Dimensions

Standard and Wheel Mount
– ISO





Ports

- G 3/4 (BSP) O-ring Ports (2)
- G 1/4 (BSP) O-ring Case Drain Port (1)
- 7/16-20 UNF -2B SAE O-ring Shift Ports (2)

Standard Rotation Viewed from Shaft End

- Port A Pressurized — CW
- Port B Pressurized — CCW



Standard Motors (ISO)



STANDARD MOTORS (ISO)

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
325 [19.8]	247,4 [9.74]	219,5 [8.64]	174,2 [6.86]
400 [24.4]	253,7 [9.99]	225,8 [8.89]	180,8 [7.12]
505 [30.7]	263,1 [10.36]	235,0 [9.25]	189,7 [7.47]
570 [34.9]	269,2 [10.60]	241,0 [9.49]	196,1 [7.72]
630 [38.5]	274,3 [10.80]	246,4 [9.70]	201,4 [7.93]
685 [41.7]	278,9 [10.98]	251,0 [9.88]	205,7 [8.10]
785 [48.0]	288,0 [11.34]	260,1 [10.24]	215,1 [8.47]
940 [57.4]	301,8 [11.88]	273,8 [10.78]	228,9 [9.01]

Wheel Motors (ISO)



WHEEL MOTORS (ISO)


Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
325 [19.8]	173,2 [6.82]	145,3 [5.72]	100,1 [3.94]
400 [24.4]	179,6 [7.07]	151,6 [5.97]	106,7 [4.20]
505 [30.7]	189,0 [7.44]	160,8 [6.33]	115,6 [4.55]
570 [34.9]	195,1 [7.68]	166,9 [6.57]	121,9 [4.80]
630 [38.5]	200,2 [7.88]	172,2 [6.78]	127,3 [5.01]
685 [41.7]	204,7 [8.06]	176,8 [6.96]	131,6 [5.18]
785 [48.0]	213,9 [8.42]	185,9 [7.32]	141,0 [5.55]
940 [57.4]	227,6 [8.96]	199,6 [7.86]	154,7 [6.09]

VIS 40 Series

Two-speed

Dimensions

Bearingless




Ports

- 1-1/16-12 UN-2B SAE O-ring Ports (2)
- 9/16-18 UNF-2B SAE O-ring Case Drain Port (1)
- 7/16-20 UNF -2B SAE O-ring Shift Ports (2)
- or G 3/4 (BSP) O-ring Ports (2)
- G 1/4 (BSP) O-ring Case Drain Port (1)
- 7/16-20 UNF -2B SAE O-ring Shift Ports (2)

Standard Rotation Viewed from Drive End

Port A Pressurized — CW

Port B Pressurized — CCW




For VIS 40 bearingless motor application information, contact your Eaton representative (mating coupling blanks available from Eaton Hydraulics).


Note:

After machining blank, part must be hardened per Eaton specification.

C	59,94	[2.36]	Dia.
D	49,00	[1.93]	Dia.
E	155,86	[6.14]	Max.
F	150,88	[5.94]	Min.
			Full Form Dia.
G	26,92	[1.06]	
H	33,30	[1.21]	
J	106,43	[4.19]	
			Full Form Dia.
K	72,64	[2.86]	
L	15		



Mating Coupling Blank
Eaton Part No. 13280-002



BEARINGLESS MOTORS



Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
325 [19.8]	177,0 [6.97]	149,1 [5.87]	103,9 [4.09]
400 [24.4]	183,6 [7.23]	155,7 [6.13]	110,7 [4.36]
505 [30.7]	193,0 [7.60]	164,8 [6.49]	119,6 [4.71]
570 [34.9]	199,1 [7.84]	170,9 [6.73]	126,0 [4.96]
630 [38.5]	204,0 [8.03]	176,0 [6.93]	131,1 [5.16]
685 [41.7]	208,8 [8.22]	180,8 [7.12]	135,6 [5.34]
785 [48.0]	217,9 [8.58]	190,0 [7.48]	145,0 [5.71]
940 [57.4]	231,6 [9.12]	203,7 [8.02]	158,8 [6.25]

VIS 40 Series Two-speed

Installation Information

Bearingless

- 1 Internal spline in mating part to be per spline data. Specification material to be ASTM A304, 8620H carburize to a hardness of 60-64 HRC with case depth (to 50HRC) of 0,076-1,27 [.030 -.050]. Dimensions apply after heat treat.
- 2 Mating part to have critical dimensions as shown. Oil holes must be provided and open for proper oil circulation.
- 3 Seal to be furnished with motor for proper oil circulation thru splines.
- 4 Similar to SAE "C" Four Bolt Flange.



Spline Pitch.....	10/20
Pressure Angle.....	30°
Number of teeth.....	16
Class of Fit.....	Ref. 5
Type of Fit.....	Side
Pitch Diameter.....	Ref. 40,640000 [1.6000000] $\text{Ⓢ} 0,20$ [.008] H
Base Diameter.....	Ref. 35,195272 [1.3856406]
Major Diameter.....	43,56 [1.715] Max. 43,18 [1.700]
Min. Minor Diameter.....	36,83 -37,08 [1.450 -1.460]
Form Diameter, Min.	42,47 [1.672]
Fillet Radius.....	0,64 -0,76 [.025 -.030]
Tip Radius.....	0,25 -0,51 [.010 -.020]
Finish.....	1,6 (63)
Involute Profile Variation.....	+0,000 -0,025 [+ .0000 -.0010]
Total Index Variation.....	0,040 [.0016]
Lead Variation.....	0,013 [.0005]
Circular Space Width:	
Maximum Actual	4.105 [1.1616]
Minimum Effective	3,995 [1.1573]
Maximum Effective	Ref. 4,056 [1.1597]
Minimum Actual	Ref. 4,081 [1.1582]
Dimension Between Two Pins.....	Ref. 34,272 -34,450 [1.3493 -1.3563]
Pin Diameter	4,389 [1.1728]

VIS 40 Series Two-speed

Product Numbers

Closed Loop

Use digit prefix —
176-, 178-, or 182- plus four
digit number from charts for
complete product number—
Example 176-0022.

**Orders will not be accepted
without three digit prefix.**

SAE

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r[in ³ /r] / PRODUCT NUMBER							
			325 [19.8]	400 [24.4]	505 [30.7]	570 [34.9]	630 [38.5]	685 [41.7]	785 [48.0]	940 [57.4]
Standard	40 mm Straight	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	-0106	-0021	-0022	-0023	-0024	-0025	-0026
	1 1/2 inch 17 Tooth Splined	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	178-0108	-0109	-0027	-0028	-0029	-0030	-0031	-0032
	1 3/4 inch Tapered	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	-0128	-0033	-0034	-0035	-0036	-0037	-0038
Wheel	40 mm Straight	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	-0002	-0003	-0004	-0005	-0006	-0007
	1 1/2 inch 17 Tooth Splined	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	-0008	-0009	-0010	-0011	-0012	-0013
	1 3/4 inch Tapered	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	182-0041	-0014	-0015	-0016	-0017	-0018	-0019
Bearingless		1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	176-0037	—	-0019	-0020	-0021	-0022	-0023	-0024

176-0022

Oversize

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r[in ³ /r] / PRODUCT NUMBER							
			325 [19.8]	400 [24.4]	505 [30.7]	570 [34.9]	630 [38.5]	685 [41.7]	785 [48.0]	940 [57.4]
Standard	40 mm Straight	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	178-0039	-0040	—	—	—	—
	46 mm 28 Tooth Splined	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	178-0045	-0046	—	—	—	—
	1 3/4 inch Tapered	1 1/16 -12 UNF O-ring (2) 9/16 -18 UNC Drain Port (1)	—	—	178-0051	-0052	—	—	—	—

ISO

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r[in ³ /r] / PRODUCT NUMBER							
			325 [19.8]	400 [24.4]	505 [30.7]	570 [34.9]	630 [38.5]	685 [41.7]	785 [48.0]	940 [57.4]
Standard	40 mm Straight	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	178-0110	-0111	-0057	-0058	-0059	-0060	-0061	-0062
	45 mm Tapered	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	178-0095	—	-0069	-0070	-0071	-0072	-0073	-0074
	1 1/2 inch 17 Tooth Splined	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0063	-0064	-0065	-0066	-0067	-0068
Wheel	40 mm Straight	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	182-0042	—	-0020	-0021	-0022	-0023	-0024	-0025
	45 mm Tapered	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0026	-0027	-0028	-0029	-0030	-0031
	1 1/2 inch 17 Tooth Splined	G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0032	-0033	-0034	-0035	-0036	-0037
Bearingless		G 3/4 (BSP) (2) G 1/4 (BSP) Drain Port (1)	—	—	-0025	-0026	-0027	-0028	-0029	-0030

176-0028

Note:


The product numbers on this page are for motors used in closed loop circuits. They include a back-pressure relief valve that is set at 4,5 bar [65 PSI].

- A case drain is required for all closed loop VIS motor applications.
- The maximum case pressure for the VIS motor is 3,5 bar [50 PSI].

VIS 40 Series Two-speed

Model Code

The following 16 - digit coding system has been developed to identify all of the configuration options for the VIS 40 two-speed motor. Use this model code to specify a motor with the desired features. All 16 digits of the code must be present when ordering. You may want to photocopy the matrix below to ensure that each number is entered in the correct box.



1, 2, 3 Product Series

ADT – VIS 40- Two-speed Motor

4, 5 Displacement – cm³/r [in³/r]

20 – 325 [19.8]

24 – 400 [24.4]

31 – 505 [30.7]

35 – 570 [34.9]

38 – 630 [38.5]

42 – 685 [41.7]

48 – 785 [48.0]

57 – 940 [57.4]

6 Mounting Type

A – 4 Bolt Bearingless 127,00 [5.000] Pilot Dia. with 12,19 [.480] Pilot Length and 14,35 [.565] Dia holes on 161,92 [6.375] Dia. Bolt Circle

B – 4 Bolt Wheel Mount 160,00 [6.3] Pilot Dia. With 5,8 [.23] Pilot Length and 18,00 [.709] Dia. Holes on 200,00 [7.874] Dia. Bolt Circle (ISO Compatible)

C – 4 Bolt Oversize Flange 185,4 [7.30] Rear Pilot Dia., 169,90 [6.689], 139,93 [5.509], 127,0 [5.00] Dia (Front Pilots) and 18,01 [.709] Dia. Holes on 224,00 [8.819] Dia. Bolt Circle

F – 4 Bolt Standard Mount (SAE CC) 127,00 [5.000] Pilot Dia. With 12,2 [.48] Pilot Length and 14,32 [.564] Dia. Holes on 161,92 [6.375] Dia.

Bolt Circle

G – 4 Bolt Wheel Mount 139,7 [5.50] Pilot Dia. with 7,9 [.31] Pilot Length and 14,32 [.564] Dia. Holes on 184,15 [7.250] Dia. Bolt Circle (SAE Compatible)

H – 4 Bolt Standard Mount 125,00 [4.92] Pilot Dia. With 8,9 [.35] Pilot Length and 14,00 [.551] Dia. Holes on 160,00 [6.299] Dia. Holes on 160,00 [6.299] Dia. Bolt Circle (ISO Compatible)

M – Standard, 4 Bolt: 169,75 [6.683] Pilot Dia. With 4,3 [.17] Pilot Length and M16 X 2 -6H Threaded Holes on 224,00 [8.819] Dia. Bolt Circle (To be selected for Brake Option)

7, 8 Output Shaft

00 – None (Bearingless)

01 – 45 mm Dia. 10:1 Tapered Shaft Per ISO R775 with M30X2-6H Threaded Shaft End, 12W X 8H X 28L [.472W X .313H X 1.102L] Key

02 – 1-3/4 inch Dia. .125:1 Tapered Shaft Per SAE J501 with 1-1/4 - 18 UNEF-2A Threaded Shaft End, 11,11 [.4375] Square X 31,8 [1.25] Straight Key

04 – 46 mm Dia. Flat Root Side Fit, 28 Tooth, 16/32 DP 30 Degree Involute Spline, 93,0 [3.66] Minimum Full Spline with M16 X 2,0-6H Thread in End

07 – 40 mm Dia. Straight Shaft with M12 X 1,75-6H Thread in End, 12W X 8H X 63L [.472W X .313H X 2.480L] Key (SAE Compatible)

08 – 1-1/2 inch Dia. Flat Root Side Fit, 17 Tooth, 12/24 DP 30 Degree Involute Spline, 39,1 [1.54] Minimum Full Spline with 3/8-16 UNC-2B Thread in End (SAE Compatible)

09 – 1-1/2 inch Dia. Flat Root Side Fit, 17 Tooth, 12/24 DP 30 Degree Involute Spline, 56,6 [2.23] Minimum Full Spline with M12 X 1.75-6H Thread in End (ISO Compatible)

10 – 40 mm Dia. Straight Shaft with M12 X 1,75-6H Thread in End, 12W X 8H X 67L [.472W X .313H X 2.630L] Key (ISO Compatible)

9 Ports

A – 1–1/16-12 UN-2B Size 12 O-ring Port, Accepts Fittings for SAE J1926

B – G 3/4 (BSP) Straight Thread Port

10 Case Flow Options

A – Shuttle Valve with 9/16-18 UNF-2B, Size 6 O-ring Port Case Drain, Accepts Fittings for SAE J1926

B – Shuttle Valve with G 1/4 (BSP) Straight Thread Port Case Drain

11 Back-Pressure Relief

1 – Set at 4,5 bar [65 PSI] (for Manual Pumps)

2 – Set at 15,2 bar [220 PSI] (for Servo Pumps)

4 – Set at 15,2 bar [300 PSI] (for high charge Servo Pumps)

12, 13 Special Features

00 – None

08 – Spring Applied Hydraulic Release Wet Brake With Brake Capacity of 20,000 lbf-in Static and 150 lbf/in² release pressure

14 _ Paint/ Special Packaging

0 – Primer, Individual Box

A – Low Gloss Black Primer, Individual Box

B – No Paint, Bulk Box Option

C – Low Gloss Black Primer, Bulk Box Option

15 _ Eaton Assigned Code when Applicable



0 – Assigned Code

16 _ Eaton Assigned Design Code

C – Assigned Design Code

VIS 40 Series

Brake Description



Brake Motor WITH Outer Grease Seal

Features

- Spring-Applied/
Hydraulically Released
Multi-Disc Brake
- Spring automatically
applies brake when hydro-
static pressure is absent
- Environmentally Protected
- Integral Design –
Motor and brake as a sin-
gle package to minimize
length and cost.
- Infinite Braking –
Eliminates machine creep
associated with park pawl
mechanisms
- Boost Feature –
Increases holding capacity
to match full motor output
torque
- No adjustments needed
- Two Sets of Release
and Boost Ports –
Allows for multiple plumb-
ing options and facilitates
bleeding
- Outer Grease Seal -
optional feature that
encloses the front bearing
protecting it from external
contamination

Applications

- Skid Steer Loaders
- Mini Excavators
- Trenchers
- Road Rollers
- Anywhere load-holding
is needed on a Low-
Speed High-Torque drive
system

Specifications


- Static Holding Torque – 780 N-m [6900 lb-in] minimum
(spring only - no boost)
2621 N-m [23200 lb-in] minimum
(@ 10,3 bar [150 PSI] boost)
3570 N-m [31600 lb-in] minimum
(@ 15,2 bar [220 PSI] boost)
- Release Pressure – 10,3 bar [150 PSI] minimum
for full release
68,9 bar [1000 PSI] maximum
allowed at release port
- Case Pressure – 1,4 bar [20 PSI] continuous
3,5 bar [50 PSI] maximum
- Boost Pressure – 15,2 bar [220 PSI] continuous
34,5 bar [500 PSI] maximum
- Speed – 360 RPM maximum
- Emergency – After 3 consecutive stops,
brake to still meet parking
requirement

Model Code Selection:

To add a brake to the motor, select Mounting Option 'M' from Mounting Options and select Brake Option from Special Features.

VIS 40 Series

Brake Dimensions



BRAKE MOTORS (SINGLE-SPEED)

Displacement cm ³ /r [in ³ /r]	A mm [inch]	B mm [inch]
325 [19.8]	220,9 [8.78]	250,2 [9.85]
400 [24.4]	229,7 [9.05]	256,9 [10.11]
505 [30.7]	238,7 [9.40]	265,9 [10.47]
570 [34.9]	244,9 [9.64]	272,1 [10.71]
630 [38.5]	250,1 [9.85]	277,3 [10.92]
685 [41.7]	254,7 [10.04]	281,9 [11.10]
785 [48.0]	264,0 [10.40]	291,2 [11.46]
940 [57.4]	277,7 [10.94]	304,9 [12.00]


BRAKE MOTORS (TWO-SPEED)

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
325 [19.8]	286,1 [11.26]	258,9 [10.20]	213,5 [8.41]
400 [24.4]	292,7 [11.52]	265,7 [10.46]	220,3 [8.67]
505 [30.7]	301,9 [11.88]	274,7 [10.82]	229,3 [9.03]
570 [34.9]	308,0 [12.12]	280,9 [11.06]	235,5 [9.27]
630 [38.5]	313,1 [12.32]	285,9 [11.27]	238,5 [9.27]
685 [41.7]	317,9 [12.52]	290,7 [11.45]	245,3 [9.66]
785 [48.0]	327,0 [12.88]	300,0 [11.80]	254,6 [10.02]
940 [57.4]	340,7 [13.42]	313,7 [12.35]	268,3 [10.56]



VIS 40 Series

Brake Shaft Dimensions/ Sideload Curves

Standard Brake




Brake with Outer Grease Seal



VIS 45 Series

Highlights



Description

The VIS 45 is the most powerful motor in the VIS Series product line. Maximum continuous output torque capability is rated to 4520 Nm [40,000 lb-in.] with a displacement range from 630cc to 1560cc per revolution. VIS 45 motors can be run up to 170 LPM [45 GPM] with pressure capability up to 310 bar [4500 PSI]. The motor utilizes patented VIS technology with improved high-strength Geroler, optimized drive geometry, and two-piece pre-loaded balance plate for increased starting efficiency, reduced leakage and higher back pressure capacity.

VIS 45 Motors

Geroler Element	5 Displacements
Flow l/min [GPM]	170 [45] Continuous
	189 [50] Intermittent
Speed	Up to 284 RPM
Pressure bar [PSI]	310 [4500] Cont.
	345 [5000] Inter.
	380 [5500] Peak
Torque Nm [lb - in]	4520 [40000] Cont.
	5650 [50000] Inter.

Features

- Patented VIS Geroler technology
- Three moving components: (Geroler, star, drive, and output shaft)
- Two-piece pre-loaded pressure balance plate
- Variety of optional features including two-speed option, and case flow solutions for both closed-loop and open-loop applications.

Benefits

- Extremely compact powerful package
- Increased torque capability
- Greatest horsepower density in the VIS motor line
- High efficiency
- Quiet, smooth operation
- Reliable performance
- Design Flexibility

Applications

- Traction Drives
- Skid Steer loaders
- Grapples
- Excavator Swing Drives
- Marine & Military Winches
- Utility Reels
- Harvesters
- Snow Grooming Equipment
- Trenchers
- Piggy-back Forklifts
- Industrial Machine Tools
- Truck Grapples
- Wood Processing – Saw Mills
- Augers



Auger



Skid Steer




Injector



Port Equipment

VIS 45 Series

Specifications



SPECIFICATION DATA — VIS 45 SERIES MOTORS

Displ. cm ³ /r [in ³ /r]		630 [38.6]	805 [48.6]	990 [60.5]	1245 [76.0]	1560 [95.0]
Max. Speed (RPM) @ Flow	Continuous	256	198	164	129	104
	Intermittent	284	220	183	143	115
Flow l/min [GPM]	Continuous	170 [45]	170 [45]	170 [45]	170 [45]	170 [45]
	Intermittent	189 [50]	189 [50]	189 [50]	189 [50]	189 [50]
Torque Nm [lb-in]	Continuous	2963 [26080]	3555 [31460]	4052 [35860]	4520 [40000]	4520 [40000]
	Intermittent	3111 [27530]	3722 [32940]	4549 [40269]	5376 [47592]	5650 [50000]
Pressure Δ bar [Δ PSI]	Continuous	310 [4500]	310 [4500]	258 [3740]	205 [2975]	164 [2380]
	Intermittent	345 [5000]	345 [5000]	322 [4675]	256 [3720]	205 [2975]
	Peak	379 [5500]	379 [5500]	379 [5500]	308 [4465]	246 [3570]
Weight kg [lb]	Standard or Wheel Mount	53,8 [118.7]	55,2 [121.6]	56,7 [125.0]	58,7 [129.4]	61,2 [134.9]
	Bearingless	28,3 [62.3]	29,6 [65.2]	31,1 [68.6]	33,1 [73.0]	35,6 [78.5]
Weight kg [lb]	Two-speed Standard or Wheel Mount	58,5 [128.9]	59,8 [131.8]	61,3 [135.2]	63,3 [139.6]	65,8 [145.1]
	Two-speed Bearingless	32,9 [72.5]	34,2 [75.4]	35,7 [78.8]	37,7 [83.2]	40,2 [88.7]

A simultaneous maximum torque and maximum speed NOT recommended.

Note:

To assure best motor life, run motor for approximately one hour at 30% of rated pressure before application to full load. Be sure motor is filled with fluid prior to any load applications.

Maximum Inlet Pressure:

400 bar [5800 PSI]
Do Not Exceed A Pressure Rating (for displacement size see chart above).

Return Pressure (Back-Pressure):

Minimum – 3,5 bar [50 PSI]
Maximum – 21 bar [300 PSI]

Note:

Return (back-pressure) must be 3,5 bar [50 PSI] greater than the case pressure, except with open loop circuit.

Δ Pressure:

The true Δ bar [Δ PSI] between inlet port and outlet port

Case Pressure:

Minimum – No Pressure
Maximum – 3,5 bar [50 PSI]

Note:

The case must be full when the motor is operating. A case drain is recommended.

Continuous Rating:

Motor may be run continuously at these ratings

Intermittent Operation:

10% of every minute

Peak Operation:

1% of every minute

Recommended Fluids:

Premium quality, anti-wear type hydraulic oil with a viscosity of not less than 70 SUS at operating temperature.

Recommended System Operating Temp.:

-34°C to 82°C [-30°F to 180°F]

Recommended Filtration:

Per ISO Cleanliness Code, 4406: 20/18/13

Shuttle:

Standard

Back-Pressure Relief Valve:


Required for closed loop circuit.

VIS 45 Series

Performance Data

Motors run with high efficiency in all areas designated with a number for torque and speed. For best motor life select a motor to run with a torque and speed range shown in the light shaded area.

Performance data is typical at 120 SUS. Actual data may vary slightly from unit to unit in production.



805 cm³/r [48.6 in³/r]
□ Pressure Bar [PSI]

	250	500	1000	1500	2000	2500	3000	3500	4000	4500	5000
	15	35	70	105	140	170	205	240	275	310	345
4	1600	3350	7180	10670	13480	16640	19680	21740	25860	28500	31720
15	181	379	811	1206	1523	1880	2224	2457	2922	3221	3584
8	1620	3380	7240	10730	13740	16920	19950	22160	25920	28970	32200
30	183	382	818	1212	1553	1912	2254	2504	2929	3274	3639
12	1640	3310	7180	10770	14170	17290	20730	23270	26340	29420	32470
45	185	374	811	1217	1601	1954	2342	2630	2976	3324	3669
16	1660	3220	7010	10680	14290	17710	21240	24170	26830	30340	32940
61	188	364	792	1207	1615	2001	2400	2731	3032	3428	3722
20	1600	3110	6840	10380	14000	17290	20990	24490	27270	31390	
76	181	351	773	1173	1582	1954	2372	2767	3082	3547	
24	1560	3030	6750	10250	13830	17340	21110	24450	27620	31460	
91	176	342	763	1158	1563	1959	2385	2763	3121	3555	
28		2720	6560	10190	13780	17390	21090	24360	27420	31238	
106		307	741	1151	1557	1965	2383	2753	3098	3529	
32		2620	6330	10000	13480	17070	20730	24180	27270	31064	
121		296	715	1130	1523	1929	2342	2732	3082	3509	
36		2620	5910	9480	13140	16640	20200	23570	26910	30646	
136		296	668	1071	1485	1880	2283	2663	3041	3462	
40			5390	9220	12790	16120	19700	23080	26343	30019	
151			609	1042	1445	1822	2226	2608	2976	3391	
45			5150	8970	12450	15780	19420	22650	25848	29462	
170			582	1014	1407	1783	2194	2559	2920	3328	
50			4770	8610	12140	15380	19180	22440			
189			539	973	1372	1738	2167	2536			
			220	217	215	215	212	212			

630 cm³/r [38.6 in³/r]

□ Pressure Bar [PSI]

	250	500	1000	1500	2000	2500	3000	3500	4000	4500	5000
	15	35	70	105	140	170	205	240	275	310	345
4	1270	2710	5530	8250	10300	12900	15540	17720	20820	23640	25740
15	144	306	625	932	1164	1458	1756	2002	2353	2671	2909
8	1290	2720	5580	8290	10490	13110	15760	18070	21000	24100	26070
30	146	307	631	937	1185	1481	1781	2042	2373	2723	2946
12	1310	2670	5440	8320	10820	13400	16370	18970	21230	24540	26840
45	148	302	615	940	1223	1514	1850	2144	2399	2773	3033
16	1320	2600	5400	8250	10910	13730	16780	19710	21970	24870	27530
61	149	294	610	932	1233	1551	1896	2227	2483	2810	3111
20	1290	2500	5270	8020	10690	13400	16730	20020	22320	25420	
76	146	283	596	906	1208	1514	1890	2262	2522	2872	
24	1240	2440	5200	7920	10560	13430	16700	19970	22610	25730	
91	140	276	588	895	1193	1518	1887	2257	2555	2907	
28		2190	5050	7870	10520	13480	16660	19860	22450	26080	
106		247	571	889	1189	1523	1883	2244	2537	2963	
32		2110	4870	7720	10300	13230	16370	19720	22320	25986	
121		238	550	872	1164	1495	1850	2228	2522	2936	
36		2090	4550	7330	10030	12890	15960	19220	22040	25655	
136		236	514	828	1133	1457	1803	2172	2491	2898	
40			4150	7120	9760	12490	15560	18820	21600	25185	
151			469	805	1103	1411	1758	2127	2441	2845	
45			3970	6930	9500	12230	15340	18470	21207	24742	
170			449	783	1074	1382	1733	2087	2396	2795	
50			3680	6660	9270	11920	15150	18300			
189			416	753	1048	1347	1712	2068			
			284	280	280	276	268	259			

(9270) Torque [lb-in]
1048 Nm
280 Speed RPM

VIS 45 Series

Performance Data

Motors run with high efficiency in all areas designated with a number for torque and speed. For best motor life select a motor to run with a torque and speed range shown in the light shaded area.

Performance data is typical at 120 SUS. Actual data may vary slightly from unit to unit in production.

Continuous

Intermittent

		1245 cm³/r [76.0 in³/r]									
		□ Pressure Bar [PSI]									
Flow LPM [GPM]		250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275	4250 295
	4	2160 244	4800 542	9960 1125	15150 1712	20200 2283	26450 2989	30670 3466	39180 4427	42800 4836	43220 4884
	15	12	11	11	11	11	10	10	9	9	9
	8	2250 254	4830 546	10370 1172	15760 1781	22010 2487	27180 3071	33330 3766	39840 4502	43660 4934	44400 5017
	30	24	23	22	22	21	20	20	19	19	19
	12	2400 271	5390 609	10910 1233	17290 1954	22780 2574	28470 3217	34170 3861	40140 4536	44160 4990	47220 5336
	45	36	33	33	32	32	32	32	31	31	30
	16	2410 272	5150 582	10930 1235	16970 1918	22880 2585	28600 3232	33900 3831	39500 4464	44510 5030	47592 5376
	61	48	46	45	44	43	43	43	42	41	40
	20	2350 266	4890 553	10650 1203	16470 1861	21960 2481	27450 3102	33130 3744	37710 4261	43890 4960	46933 5302
Flow LPM [GPM]	76	60	59	57	56	56	56	55	55	54	52
	24	2190 247	4760 538	10460 1182	15920 1799	21230 2399	26530 2998	32320 3652	37680 4258	42670 4822	45673 5156
	91	72	70	68	67	67	67	66	66	65	63
	28	1990 225	4260 481	10070 1138	15860 1792	21200 2396	26420 2985	32480 3670	37500 4238	42464 4797	45418 5131
	106	85	82	80	78	78	78	77	77	76	74
	32		4100 463	9770 1104	15410 1741	20770 2347	26300 2972	31920 3607	37240 4208	42167 4764	45103 5095
	121		94	91	90	89	89	88	88	87	84
	36		4090 462	9060 1024	14650 1655	20060 2267	25670 2901	31110 3515	36295 4100	41087 4642	43955 4966
	136		106	103	101	101	100	99	99	98	95
	40			8300 938	14150 1599	19570 2211	24900 2814	30320 3426	35373 3996	40034 4523	42836 4839
Flow LPM [GPM]	151			114 113	112 111	111 110	110 110	110 108	108 105		
	45			8100 915	13970 1579	19310 2182	24610 2781	29972 3686	34967 3950	39570 4470	42343 4783
	170			129 127	126 125	126 125	124 124	124 124	122 122	118	
	50			7900 893	13790 1558	19050 2153	24310 2747				
	189			143 141	140 140						

990 cm³/r [60.5 in³/r]												
□ Pressure Bar [PSI]												
Flow LPM [GPM]		250 15	500 35	1000 70	1500 105	2000 140	2500 170	3000 205	3500 240	4000 275	4500 310	4750 330
	4	2000 226	4100 463	8630 975	12620 1426	16050 1814	20080 2269	24150 2729	28320 3200	32590 3683	35150 3972	37040 4186
	15	15 15	15 15	15 15	15 15	14 14	14 14	14 14	13 13	12 12	11 11	10 10
	8	2020 228	4130 467	8700 983	12740 1440	16350 1848	20420 2307	24480 2766	28400 3209	32850 3712	35670 4031	37250 4209
	30	30 30	30 30	29 29	29 29	29 29	28 28	28 28	27 27	25 25	25 25	24 24
	12	2050 232	4050 458	8630 975	12780 1444	16870 1906	20860 2357	25440 2875	28550 3226	32920 3720	35860 4052	37630 4252
	45	45 45	45 45	44 44	44 44	43 43	43 43	41 41	41 41	41 41	40 40	39 39
	16	2070 234	3940 445	8420 951	12680 1433	17010 1922	21380 2416	26070 2946	29660 3352	33020 3731	36620 4138	38439 4342
	61	61 61	60 60	58 58	58 58	58 58	57 57	55 55	55 55	54 54	53 53	52 52
	20	2000 226	3800 429	8220 929	12330 1393	16660 1883	20860 2357	25760 2911	30060 3397	33550 3791	37880 4280	39766 4492
76	76 76	75 75	73 73	73 73	72 72	71 71	69 69	69 69	68 68	66 66	64 64	
24	1950 220	3700 418	8120 918	12180 1376	16460 1860	20890 2361	25820 2918	30090 3400	33990 3841	38366 4334	40269 4549	
91	91 91	90 90	88 88	88 88	86 86	85 85	83 83	83 83	82 82	80 80	78 78	
28		3320 375	7880 890	12100 1367	16400 1853	20990 2372	25890 2926	29900 3379	33750 3814	39106 4280	39995 4518	
106		105 105	102 102	102 102	101 101	99 99	97 97	97 97	95 95	92 92	90 90	
32		3210 363	7610 860	11870 1341	16050 1814	20600 2328	25440 2875	29680 3354	33550 3791	37890 4280	39766 4492	
121		120 120	117 117	117 117	115 115	114 114	110 110	110 110	109 109	106 106	103 103	
36		3200 362	7100 802	11260 1272	15640 1767	20080 2269	24800 2802	28930 3269	32716 3696	36936 4173	38759 4379	
136		135 135	131 131	131 131	130 130	128 128	124 124	124 124	123 123	119 119	116 116	
40			6480 732	10950 1237	15220 1720	19460 2199	24170 2731	28330 3201	32023 3618	36155 4084	37935 4286	
151			146 146	146 146	144 144	142 142	138 138	138 138	137 137	133 133	130 130	
45			6190 699	10650 1203	14810 1674	19040 2152	23830 2693	27952 3158	31599 3570	35679 4031	37432 4229	
170			164 164	164 164	162 162	160 160	155 155	155 155	154 154	149 149	145 145	
50			5740 649	10230 1156	14450 1633	18570 2098	23540 2660					
189			183 183	183 183	180 180	178 178	173 173					

[18570]
2098
178

Torque [lb-in]
Nm
Speed RPM

VIS 45 Series

1560 cm³/r [95.0 in³/r]

Performance Data

Motors run with high efficiency in all areas designated with a number for torque and speed. For best motor life select a motor to run with a torque and speed range shown in the light shaded area.

Performance data is typical at 120 SUS. Actual data may vary slightly from unit to unit in production.

	Continuous
	Intermittent

□ Pressure Bar [PSI]


	250	500	1000	1500	2000	2500	3000	3500	4000
	15	35	70	105	140	170	205	240	275
4	2700	5670	11910	18520	24910	30860	37610	42320	48366
15	305	641	1346	2093	2815	3487	4250	4782	5464
	9	9	9	9	9	8	8	8	8
8	2810	5910	12400	19260	25590	31740	39310	44150	50457
30	318	668	1401	2176	2892	3587	4442	4989	5700
	19	19	18	18	18	17	16	15	15
12	3010	6300	13040	20490	26600	33070	39880	46670	53337
45	340	712	1474	2315	3006	3737	4506	5274	6025
	29	28	28	27	26	25	23	22	22
16	3020	6300	13360	20740	27270	33950	40450	48630	55577
61	341	712	1510	2344	3082	3836	4571	5495	6279
	38	38	37	36	35	34	31	29	29
20	2930	6150	13200	20490	27110	34830	39820	47662	54470
76	331	695	1492	2315	3063	3936	4500	5384	6154
	48	47	46	45	44	42	39	37	37
24	2780	5910	12880	19750	26930	34390	39310	47300	54057
91	314	668	1455	2232	3043	3886	4442	5343	6107
	58	56	55	54	53	50	47	44	44
28		5310	12500	19630	26600	33950	38740	46635	53297
106		600	1413	2218	3006	3836	4378	5268	6021
		66	64	63	62	59	55	52	52
32		5120	12070	19260	26260	33510	38180	45982	52550
121		579	1364	2176	2967	3787	4314	5195	5937
		75	74	72	70	67	62	58	58
36		5100	11270	18270	25590	33070	37652	45366	
136		576	1274	2065	2892	3737	4254	5125	
		85	83	81	79	76	70	66	
40			10280	17760	24910	32630	37124	44750	
151			1162	2007	2815	3687	4194	5055	
			92	90	88	84	78	73	
45			9820	17280	24240	31793	36119	43577	
170			1110	1953	2739	3592	4080	4923	
			104	101	99	95	87	82	
50			9100	16600	23650				
189			1028	1876	2672				
			115	113	110				

16600 } Torque [lb-in]
1876 } Nm
113 } Speed RPM

VIS 45 Series

Dimensions

Standard Mount



Ports

1-5/16-12 UN-2B SAE O-ring Ports (2)

9/16-18 UNF-2B SAE O-ring Case Drain Port (1)



Or G 1 (BSP) O-ring Ports (2)

G 1/4 (BSP) O-ring Case Drain Port (1)

Standard Rotation Viewed from Shaft End

Port A Pressurized — CW

Port B Pressurized — CCW




STANDARD MOTORS

Displacement cm ³ /r [in ³ /r]	X Max. mm [inch]	Y mm [inch]
630 [38.6]	260,9 [10.27]	228,6 [9.00]
805 [48.6]	271,3 [10.68]	239,0 [9.41]
990 [60.5]	283,7 [11.17]	251,5 [9.90]
1245 [76.0]	299,7 [11.80]	267,7 [10.54]
1560 [95.0]	319,5 [12.58]	287,5 [11.32]

VIS 45 Series

Dimensions

Wheel Mount





Ports

- 1-5/16-12 UN-2B SAE O-ring Ports (2)
- 9/16-18 UNF-2B SAE O-ring Case Drain Port (1)
- Or G 1 (BSP) O-ring Ports (2)
- G 1/4 (BSP) O-ring Case Drain Port (1)

Standard Rotation Viewed from Shaft End

Port A Pressurized — CW

Port B Pressurized — CCW




WHEEL MOTORS

Displacement cm ³ /r [in ³ /r]	X Max. mm [inch]	Y mm [inch]
630 [38.6]	184,2 [7.25]	151,9 [5.98]
805 [48.6]	194,6 [7.66]	162,3 [6.39]
990 [60.5]	207,0 [8.15]	174,8 [6.88]
1245 [76.0]	223,0 [8.78]	191,0 [7.52]
1560 [95.0]	242,8 [9.56]	210,8 [8.30]

VIS 45 Series

Dimensions

Bearingless



Ports

1-5/16-12 UN-2B SAE O-ring Ports (2)

9/16-18 UNF-2B SAE O-ring Case Drain Port (1)

Or G 1 (BSP) O-ring Ports (2)

G 1/4 (BSP) O-ring Case Drain Port (1)

Standard Rotation Viewed from Drive End



Port A Pressurized — CW

Port B Pressurized — CCW

For VIS 45 bearingless motor application information, contact your Eaton representative (mating coupling blanks available from Eaton Hydraulics).




Note:

After machining blank, part must be hardened per Eaton specification.



Mating Coupling Blank Eaton Part No. 13521-003

- C** 116,3 [4.58] Dia. Max.
- D** 111,8 [4.40] Dia. Min.
- E** 37,64 [1.482] Dia.
- F** 136,7 [5.38] Max.
- G** 131,6 [5.18] Min. Full Form Dia.
- H** 64,8 [2.55]
- J** 26,4 [1.04]
- K** 109,7 [4.32] Max.
- L** 104,6 [4.12] Min. Full Form Dia.
- M** 92,58 [3.645] Dia.
- N** 73,28 [2.885] Dia.



BEARINGLESS MOTORS



Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]
630 [38.6]	161,5 [6.36]	130,3 [5.13]
805 [48.6]	172,5 [6.79]	141,2 [5.56]
990 [60.5]	184,4 [7.26]	153,4 [6.04]
1245 [76.0]	200,7 [7.90]	169,7 [6.68]
1560 [95.0]	220,5 [8.68]	189,5 [7.46]

VIS 45 Series

Installation Information

Bearingless

- 1 Internal spline in mating part to be per spline data. Specification material to be ASTM A304, 8620H carburize to a hardness of 59-62 HRC with case depth (to 50HRC) of 0,76-1,27 [.030 -.050]. Dimensions apply after heat treat.
- 2 Mating part to have critical dimensions as shown. Oil holes must be provided and open for proper oil circulation.
- 3 Seal to be furnished with motor for proper oil circulation thru splines.
- 4 Dimension indicated applies within area shown.




Spline Pitch.....	8/16
Pressure Angle.....	30°
Number of teeth.....	16
Class of Fit.....	Ref. 5
Type of Fit.....	Side
Pitch Diameter.....	Ref. 50,80000 [2.000000] $\text{Ⓢ} 0,33 [.013] \text{ B}$
Base Diameter.....	Ref. 43,994090032 [1.7320508]
Major Diameter.....	56,34±0,15 [2.218±.006]
Min. Minor Diameter.....	48,44±0,08 [1.907±.003]
Form Diameter, Min.	55,22 [2.174]
Fillet Radius.....	1,02±0,25 [.040±.010]
Tip Radius.....	0,38±0,13 [.015±.005]
Finish.....	1,6 (63)
Involute Profile Variation.....	+0,000 -0,025 [+ .0000 -.0010]
Total Index Variation.....	0,041 [.0016]
Lead Variation.....	0,015 [.0006]
Circular Space Width:	
Maximum Actual.....	6,180 [.2433]
Minimum Effective.....	6,048 [.2381]
Maximum Effective.....	Ref. 6,099 [.2401]
Minimum Actual.....	Ref. 6,114 [.2407]
Dimension Between Two Pins.....	Ref. 42,659 ±0,05 [1.6795±.0020]
Pin Diameter.....	6,223 [.2450]

VIS 45 Series


Dimensions Shafts

Splined

70 mm 22 Tooth Splined



2-3/4 Inch 32 Tooth Splined




VIS 45 Series


Dimensions Shafts

Keyed

2-5/8 Inch Straight



60 mm Tapered



VIS 45 Series

Side Load Capacity



These curves indicate the radial load capacity on the motor shaft(s) at various locations.

The curve is based on B 10 bearing life (2000 hours or 12,000,000 shaft revolutions at 100 RPM) at rated output torque.

To determine radial load at speeds other than 100 RPM, multiply the load values given on the bearing curve by the factors in the chart below.

RPM	Multiplication Factor
50	1.23
100	1.00
200	0.81
300	0.72
400	0.66
500	0.62
600	0.58
700	0.56
800	0.54

For 3,000,000 shaft revolutions or 500 hours — Increase these shaft loads 52%.



VIS 45 Series

Product Numbers

Closed Loop

Use three-digit prefix (155-, 156-, or 157-) plus four-digit number from charts for complete product number (ex: 157-0034).

Orders will not be accepted without the three-digit prefix.

SAE

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r [in ³ /r] / PRODUCT NUMBER				
			630 [38.6]	805 [48.6]	990 [60.5]	1245 [76.0]	1560 [95.0]
Standard	2-5/8 inch Straight	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	155-0107	-0108	-0109	-0110	-0111
	60 mm Tapered	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	155-0114	-0115	-0116	-0117	-0118
	70 mm 22 Tooth Splined	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	155-0121	-0122	-0123	-0124	-0125
	2-3/4 inch 32 Tooth Splined	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	155-0128	-0085	-0129	-0130	-0131
Wheel	2-5/8 inch Straight	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	156-0039	-0040	-0041	-0042	-0043
	60 mm Tapered	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	156-0046	-0047	-0048	-0049	-0050
Bearingless	(8 Bolt)	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	157-0066	-0067	-0068	-0069	-0070
	(4 Bolt)	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	157-0004	-	-	-	-

157-0004

ISO

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r [in ³ /r] / PRODUCT NUMBER				
			630 [38.6]	805 [48.6]	990 [60.5]	1245 [76.0]	1560 [95.0]
Standard	2-5/8 inch Straight	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	155-0134	-0135	-0136	-0137	-0138
	60 mm Tapered	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	155-0141	-0142	-0143	-0144	-0145
	70 mm 22 Tooth Splined	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	155-0148	-0149	-0150	-0151	-0152
	2-3/4 inch 32 Tooth Splined	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	155-0155	-0156	-0157	-0158	-0159
Wheel	2-5/8 inch Straight	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	156-0053	-0054	-0055	-0056	-0057
	60 mm Tapered	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	156-0060	-0061	-0062	-0063	-0064
Bearingless	(8 Bolt)	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	157-0074	-0075	-0076	-0077	-0078
	(4 Bolt)	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	157-0081	-	-	-	-

157-0081

Note:

The product numbers on this page are for motors used in closed loop circuits. They include a back-pressure relief valve that is set at 15,2 bar [220 PSI].

- A case drain is required for all closed loop VIS motor applications.
- The maximum case pressure for the VIS motor is 3,5 bar [50 PSI].

VIS 45 Series

Model Code

The following 16 - digit coding system has been developed to identify all of the configuration options for the VIS 45 motor. Use this model code to specify a motor with the desired features. All 16 digits of the code must be present when ordering. You may want to photocopy the matrix below to ensure that each number is entered in the correct box.

A C B			* *		*	* *		*	*	*	0 0		*	0	E
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16

1, 2, 3 Product Series

ACB – VIS 45 Motor

4, 5 Displacement cm³/r [in³/r]

39 – 630 [38.6]

49 – 805 [48.6]

60 – 990 [60.5]

76 – 1245 [76.0]

95 – 1500 [95.0]

6 Mounting Type

A – 4 Bolt Bearingless
158,70 [6.250] Pilot Dia.
With 9,07 [.355] Pilot Length
and 17,53 [.690] Dia holes
on 190,50 [7.500] Dia. B. C.
- Max. Torque Allowed 3615
Nm [32000 lb - in] (Displ.
Code 32, 35, 39 Only)

C – 8 Bolt Bearingless
158,70 [6.250] Pilot Dia.
With 9,07 [.355] Pilot Length
and 17,53 [.690] Dia holes
on 190,50 [7.500] Dia. Bolt
Circle

D – 4 Bolt Wheel Mount
200,0 [7.87] Pilot Dia. With
9,0 [.35] Pilot Length and
20,57 [.810] Dia. Holes on
250,0 [9.84] Dia. Bolt Circle

H – 4 Bolt Standard Mount
200,0 [7.87] Pilot Dia. With
9,0 [.35] Pilot Length and
20,57 [.810] Dia. Holes on
250,00 [9.84] Dia. Bolt Circle

7, 8 Output Shaft

00 – None (Bearingless)

05 – 2-5/8 inch Dia. Straight
Shaft with 5/8-18 UNF-2B
Thread in End and 15,88
[.625] Sq. X 81,3 [3.20]
Straight Key

06 – 70 mm Dia. 22 Tooth
3 Modulus Splined Shaft Per
DIN 5480 with M16 X 1,5
Thread in End

08 – 2-3/4 inch Dia. Flat
Root Side Fit 32 Tooth 12/24
DP 30°. Involute Spline with
5/8-18 UNF-2B Thread in End

09 – 60 mm Dia. 10:1
Tapered Shaft Per ISO R775
with M42 x 3 - 6H Threaded
Shaft End, 16W x 10H x 32L
[.630W x .394H x 1.260L]

9 Ports

A – 1-5/16-12 UN-2B O-ring
Port, Accepts Fittings for
SAE J1926/1

B – G 1 (BSP) Ports, Accepts
Fittings with Elastomeric or
Deformable Metallic Sealing
Member Per DIN 3852

10 Case Flow Options

B – Check valve with
leakage orifice, no case
drain (for Open Loop only)

D – Shuttle Valve with Side
Facing 9/16-18 UNF-2B,
O-ring Port Case Drain,
Accepts Fittings for SAE
J1926/1, Case Drain
Required

H – Shuttle Valve with Side
Facing G 1/4 (BSP) Port
Case Drain, Case Drain
Required

11 Back-Pressure Relief

0 – None (for Open Loop
Only)

1 – Set at 15,2 bar [220 psi]
(for Servo Pumps)

3 – Set at 4,5 bar [65 psi]
(for Manual Pumps)

4 – Set at 20,7 bar [300 PSI]
(for High Pressure Servo
Pumps)

12, 13 Special Features

00 – None

14 Paint/ Special Packaging

0 – Primer, Individual Box

A – Low Gloss Black Primer,
Individual Box

B – No Paint, Bulk Box
Option

C – Low Gloss Black Primer,
Bulk Box Option


15 Eaton Assigned Code when Applicable

0 – Assigned Code

16 Eaton Assigned Design Code

E – Assigned Design Code

VIS 45 Series Two-speed



Specifications

VIS 45 Series motors are available with an integral two-speed feature that allows the operator to shift the motor between low speed high torque (LSHT) mode and high speed low torque (HSLT) mode. In the LSHT mode, output torque and rotation speed values are equal to those of the conventional VIS 45 motor. In the HSLT mode motor displacement is reduced by one third, resulting in a fifty percent increase in rotation speed and a torque output reduction of one third. The VIS 45 two speed motor is bidirectional. It will function with equal shaft output in either rotation direction (CW or CCW) in both LSHT and HSLT modes. Shift on the fly technology allows full-power operation throughout the full duration of the shift.

Changing between modes is accomplished by changing the displacement in a ratio of 1 to 1.5. An external two-position three-way control valve is required for shifting pressure to the pilot port between low pressure (LSHT mode) and pilot signal pressure (HSLT mode). An integral selector valve shifts the motor from LSHT mode to HSLT mode. Initially, low pressure is supplied to the pilot port. The selector valve is biased to LSHT mode by a return spring. When pilot signal pressure is supplied to the pilot port and 3,5 Δbar [50 ΔPSI] is reached, the selector valve overcomes return spring force and the shifts the spool to select HSLT mode. Oil on the opposite side of the spool is drained to tank via the drain port. The pressure difference between the pilot port and drain port must be maintained to keep the motor in the high speed mode. When pilot pressure

is removed from the pilot port, the pressure in the pilot end of the spool valve is relieved and drained back through the control valve and the return spring forces the spool valve to LSHT position.

Pilot pressure may come from any source that will provide uninterrupted pressure during the high-speed mode operation. Allowable pilot pressure must be at least 3,5 Δbar [50 ΔPSI] and may be as high as full operating pressure of the motor.

All VIS 45 Series two speed motors are equipped with a return line shuttle for closed circuit applications as standard equipment. All options available on the conventional VIS 45 are also available on VIS 45 two speed motors.

Performance Data

In the LSHT mode, torque and speed values are equal to those of the conventional VIS 45 motor. In the HSLT mode, rotation speed is increased by fifty percent and torque output is reduced by one third.


The VIS 45 two speed motor will function with equal shaft output in either rotation direction (CW or CCW) in both LSHT and HSLT modes.

VIS 45 Series

Two-speed

Dimensions

Standard Mount





Ports

1-5/16-12 UN-2B SAE O-ring Ports (2)
 9/16-18 UNF-2B SAE O-ring Case Drain Port (1)
 7/16-20 UNF -2B SAE O-ring Shift Ports (2)
 or
 G 1 (BSP) O-ring Ports (2)
 G 1/4 (BSP) O-ring Case Drain Port (1)
 7/16-20 UNF -2B SAE O-ring Shift Ports (2)

Standard Rotation Viewed from Shaft End

Port A Pressurized — CW
 Port B Pressurized — CCW



STANDARD MOUNT


Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
630 [38.6]	295,5 [11.63]	263,2 [10.36]	216,3 [8.51]
805 [48.6]	305,9 [12.04]	273,6 [10.77]	226,7 [8.92]
990 [60.5]	318,3 [12.53]	286,0 [11.26]	239,1 [9.41]
1245 [76.0]	334,3 [13.16]	302,0 [11.89]	255,1 [10.04]
1560 [95.0]	353,3 [13.94]	321,0 [12.67]	274,1 [10.82]

VIS 45 Series

Two-speed

Dimensions

Wheel Mount






Ports

1-5/16-12 UN-2B SAE O-ring Ports (2)
 9/16-18 UNF-2B SAE O-ring Case Drain Port (1)
 7/16-20 UNF -2B SAE O-ring Shift Ports (2)
 or
 G 1 (BSP) O-ring Ports (2)
 G 1/4 (BSP) O-ring Case Drain Port (1)
 7/16-20 UNF -2B SAE O-ring Shift Ports (2)

Standard Rotation Viewed from Shaft End

Port A Pressurized — CW
 Port B Pressurized — CCW



WHEEL MOUNT

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
630 [38.6]	218,8 [8.61]	186,5 [7.34]	139,6 [5.49]
805 [48.6]	229,2 [9.02]	196,9 [7.75]	150,0 [5.90]
990 [60.5]	241,6 [9.51]	209,4 [8.24]	162,4 [6.39]
1245 [76.0]	257,6 [10.14]	225,6 [8.88]	178,4 [7.02]
1560 [95.0]	276,6 [10.92]	245,4 [9.66]	197,4 [7.80]


D-2

VIS 45 Series

Two-speed

Dimensions

Bearingless



Ports

- 1-1/16-12 UN-2B SAE O-ring Ports (2)
- 9/16-18 UNF-2B SAE O-ring Case Drain Port (1)
- 7/16-20 UNF -2B SAE O-ring Shift Ports (2)
- Or
- G 3/4 (BSP) O-ring Ports (2)
- G 1/4 (BSP) O-ring Case Drain Port (1)
- 7/16-20 UNF -2B SAE O-ring Shift Ports (2)


Standard Rotation Viewed from Drive End

- Port A Pressurized — CW
- Port B Pressurized — CCW

For VIS 45 two-speed bearingless motor application information, contact your Eaton representative (mating coupling blanks available from Eaton Hydraulics).

Note:

After machining blank, part must be hardened per Eaton specification.






Shaft Face Seal
Furnished with Motor

223,0/221,5
[8.78/8.72]
Dia.

Mating Coupling Blank Eaton Part No. 13521-003

- C** 116,3 [4.58] Dia. Max.
- D** 111,8 [4.40] Dia. Min.
- E** 37,64 [1.482] Dia.
- F** 136,7 [5.38] Max.
- G** 131,6 [5.18] Min. Full Form Dia.
- H** 64,8 [2.55]
- J** 26,4 [1.04]
- K** 109,7 [4.32] Max.
- L** 104,6 [4.12] Min. Full Form Dia.
- M** 92,58 [3.645] Dia.
- N** 73,28 [2.885] Dia.



BEARINGLESS MOTORS

Displacement cm ³ /r [in ³ /r]	X mm [inch]	Y mm [inch]	Z mm [inch]
630 [38.6]	196,1 [7.72]	165,9 [6.53]	116,9 [4.60]
805 [48.6]	206,5 [8.13]	176,3 [6.94]	127,3 [5.01]
990 [60.5]	218,9 [8.62]	188,8 [7.43]	139,7 [5.50]
1245 [76.0]	235,2 [9.26]	205,0 [8.07]	156,0 [6.14]
1560 [95.0]	255,0 [10.04]	224,8 [8.85]	175,8 [6.92]

VIS 45 Series Two-speed

Product Numbers

(Closed Loop)

Use digit prefix—173-,174- or 183- plus four digit number from charts for complete product number—

Example: 173-0013.

Orders will not be accepted without three digit prefix.

SAE

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r [in ³ /r] / PRODUCT NUMBER				
			630 [38.6]	805 [48.6]	990 [60.5]	1245 [76.0]	1560 [95.0]
Standard	2-5/8 inch Straight	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	174-0006	-0007	-0008	-0009	-0010
	60 mm Tapered	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	174-0011	-0012	-0013	-0014	-0015
	70 mm 22 Tooth Splined	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	174-0016	-0017	-0018	-0019	-0020
Wheel	2-3/4 inch 32 Tooth Splined	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	174-0021	-0022	-0023	-0024	-0025
	2-5/8 inch Straight	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	183-0006	-0007	-0008	-0009	-0010
	60 mm Tapered	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	183-0011	-0012	-0013	-0014	-0015
Bearingless	(8 Bolt)	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	173-0008	-0009	-0010	-0011	-0012
	(4 Bolt)	1-5/16-12 UNF O-ring (2) 9/16-18 UNC Drain Port (1)	173-0013	-	-	-	-

173-0013

ISO

MOUNTING	SHAFT	PORT SIZE	DISPL. cm ³ /r [in ³ /r] / PRODUCT NUMBER				
			630 [38.6]	805 [48.6]	990 [60.5]	1245 [76.0]	1560 [95.0]
Standard	2-5/8 inch Straight	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	174-0026	-0027	-0028	-0029	-0030
	60 mm Tapered	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	174-0031	-0032	-0033	-0034	-0035
	70 mm 22 Tooth Splined	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	174-0036	-0037	-0038	-0039	-0040
Wheel	2-3/4 inch 32 Tooth Splined	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	174-0041	-0042	-0043	-0044	-0045
	2-5/8 inch Straight	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	183-0016	-0017	-0018	-0019	-0020
	60 mm Tapered	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	183-0021	-0022	-0023	-0024	-0025
Bearingless	(8 Bolt)	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	173-0014	-0015	-0016	-0017	-0018
	(4 Bolt)	G 1 (BSP) (2) G 1/4 (BSP) Drain Port (1)	173-0019	-	-	-	-

173-0019

Note:


The product numbers on this page are for motors used in closed loop circuits. They include a back-pressure relief valve that is set at 15,2 bar [220 PSI].

- A case drain is required for all closed loop VIS motor applications.
- The maximum case pressure for the VIS motor is 3,5 bar [50 PSI].

VIS 45 Series Two-speed

Model Code

The following 18-digit coding system has been developed to identify all of the configuration options for the VIS 45 Two-Speed motor. Use this model code to specify a motor with the desired features. All 18 digits of the code must be present when ordering. You may want to photocopy the matrix below to endure that each number is entered in the correct box.



1, 2, 3 Product Series

ADP – VIS 45 Two-speed Motor

4 Eaton Assigned Code

1 – Assigned Code

5, 6 Displacement cm³/r [in³/r]

49 – 805 [48.6]

60 – 990 [60.5]

76 – 1245 [76.0]

95 – 1560 [95.0]

7 Mounting Type

A – 4 Bolt Bearingless
158,70 [6.250] Pilot Dia.
With 9,07 [.355] Pilot Length
and 17,53 [.690] Dia holes
on 190,50 [7.500] Dia. B. C.
- Max. Torque Allowed 3615
Nm [32000 lb-in] (Displ.
Code 32, 35, 39 Only)

C – 8 Bolt Bearingless
158,70 [6.250] Pilot Dia.
With 9,07 [.355] Pilot Length
and 17,53 [.690] Dia holes
on 190,50 [7.500] Dia. Bolt
Circle

D – 4 Bolt Wheel Mount
200,0 [7.87] Pilot Dia. With
9,0 [.35] Pilot Length and
20,57 [.810] Dia. Holes on
250,0 [9.84] Dia. Bolt Circle

H – 4 Bolt Standard Mount
200,0 [7.87] Pilot Dia. With
9,0 [.35] Pilot Length and
20,57 [.810] Dia. Holes on
250,00 [9.84] Dia. Bolt Circle

8, 9 Output Shaft

00 – None (Bearingless)

05 – 2-5/8 inch Dia. Straight
Shaft with 5/8-18 UNF-2B
Thread in End and 15,88
[.625] Sq. X 81,3 [3.20]
Straight Key

06 – 70 mm Dia. 22 Tooth
3 Modulus Splined Shaft Per
DIN 5480 with M16 X 1,5
Thread in End

08 – 2-3/4 inch Dia. Flat
Root Side Fit 32 Tooth 12/24
DP 30°. Involute Spline with
5/8-18 UNF-2B Thread in End

09 – 60 mm Dia. 10:1
Tapered Shaft Per ISO R775
with M42 x 3 - 6H Threaded
Shaft End, 16W x 10H x 32L
[.630W x .394H x 1.260L]

10 Ports

A – 1-5/16-12 UN-2B O-ring
Port, Accepts Fittings for
SAE J1926/1

B – G 1 (BSP) Straight
Thread Ports

11 Case Flow Options

D – Shuttle Valve with Side
Facing 9/16-18 UNF-2B,
O-ring Port Case Drain,
Accepts Fittings for SAE
J1926/1, Case Drain
Required

F – Shuttle Valve with Side
Facing G 1/4 (BSP) Port
Case Drain, Case Drain
Required

12 Back-Pressure Relief

1 – Set at 15,2 bar [220 psi]
(for Servo Pumps)

3 – Set at 4,5 bar [65 psi]
(for Manual Pumps)

4 – Set at 20,7 bar [300 PSI]
(for High Pressure Servo
Pumps)

13 Eaton Assigned Code

0 – Assigned Code

14, 15 Special Features

00 – None

16 Paint/ Special Packaging

0 – Primer, Individual Box

A – Low Gloss Black Primer,
Individual Box

B – No Paint, Bulk Box
Option

C – Low Gloss Black Primer,
Bulk Box Option

17 Eaton Assigned Code when Applicable

0 – Assigned Code

18 Eaton Assigned Design Code

B – Assigned Design Code